




3 1761 11652061 0

A20N
DT
V22

VEHICLE DIMENSIONS AND WEIGHT LIMITS IN ONTARIO



 Ontario

March 1995



Published by

Compliance Branch
Ministry of Transportation
1201 Wilson Avenue
M3M 1J8

© 1987, Queen's Printer for Ontario
ISBN 0-7778-3687-4

FOREWORD

This booklet is designed to assist commercial vehicle operators in complying with the regulations governing the size and weight of vehicles on Ontario's highways.


The booklet consists of two parts. Part I is a simplification of the vehicle weight laws set out in the Ontario Highway Traffic Act. It describes through the use of examples, how maximum allowable axle weights and gross vehicle weights are determined. Part II of the booklet contains extracts from the Ontario Highway Traffic Act regarding vehicle and load dimensions.

NOTE:

This publication has been prepared for purpose of convenience only. For accurate reference, recourse should be made to the Highway Traffic Act.

The Highway Traffic Act may be purchased from the Ontario Government Bookstore at 880 Bay Street, Toronto, Ontario M7A 1N8 Telephone: 416/326-5320.

Version française disponible



Digitized by the Internet Archive
in 2023 with funding from
University of Toronto

<https://archive.org/details/31761116520610>

DEFINITIONS - HIGHWAY TRAFFIC ACT

AXLE	Means an assembly of two or more wheels whose centres are in one transverse vertical plane and which are transmitting weight to the highway.
AXLE UNIT	Means any single axle, dual axle or triple axle.
AXLE UNIT WEIGHT	Means that part of the gross vehicle weight in kilograms transmitted to the highway by an axle unit.
AXLE GROUP WEIGHT	Means that part of the gross vehicle weight in kilograms transmitted to the highway by a two axle group, three axle group or four axle group.
FRONT AXLE	Means the front axle unit of a motor vehicle.
GROSS VEHICLE WEIGHT	Means the total weight in kilograms transmitted to the highway by a vehicle or combination of vehicles, and load.

(In this booklet, "Act" refers to the Highway Traffic Act (HTA) and "Reg" refers to Regulation 597 made under the HTA.)

WEIGHT RESTRICTION BY WIDTH OF TIRES

- (a) Vehicles equipped with tires of less than 150 mm in width shall not be operated on a highway where the weight upon any millimetre in the width of the tire exceeds 9 kg.

and

- (b) Vehicles equipped with tires of 150 mm or more in width shall not be operated on a highway where the weight upon any millimetre in the width exceeds 11 kg.

Example:

Tire Size 11.00 x 22

Tire Tread width = 11 inches

11 inches = 279.4 mm.

$279.4 \text{ mm} \times 11 \text{ kg} = 3\,073.4 \text{ kg}.$

Maximum weight on tire = 3 073.4 kg

AXLE UNITS


Axle Unit Types

1. Single Axle
2. Dual Axle
3. Triple Axle

1) Single Axle

Maximum single axle weight,

- a) for a single axle with single tires
...9 000 kg
- b) for a single axle with dual tires
...10 000 kg



Single Axle
(Single Tires)

Single Axle
(Dual Tires)

NOTE: The maximum allowable axle unit weight for a single front axle shall not exceed 5000 kg unless the driver is able to produce verification as to the manufacturer's gross weight rating for the single axle.


2) Dual Axle

Any two consecutive axles whose centres are more than 1 metre apart, and that

- (i) are articulated from a common attachment to the vehicle, or
- (ii) are designed to automatically equalize the load between the two axles.

Maximum dual axle weight shall not exceed that weight shown in Column Two opposite the corresponding axle spacing shown in Column One of Table 1 (Act), page 22.

NOTE: The maximum weight for a dual axle equipped with single tires shall not exceed 18 000 kg.




3) Triple Axle

Any three consecutive axles that have their consecutive centres equally spaced, at more than 1 metre apart, and that

- (i) are articulated from an attachment to the vehicle common to the consecutive axles, or
- (ii) are designed to automatically equalize the load between the three axles under all conditions of loading.

Maximum triple axle weight shall not exceed that weight shown in Column Two opposite the corresponding axle spacing shown in Column One of Table 2 (Act), page 22.

NOTE: The maximum weight for a triple axle equipped with single tires shall not exceed 27 000 kg.



AXLE GROUPS

Axle Group Types


1. Two Axle Group
2. Three Axle Group
3. Four Axle Group

1) Two Axle Group

Means two consecutive single axles, not including the front axle of a motor vehicle,

- (i) that are entirely within either a motor vehicle or trailer or semi-trailer,
- (ii) in which the spacings between the consecutive axles is less than 2 metres and
- (iii) which are not included in a three axle group or four axle group.

The maximum weight for a two axle group shall not exceed that weight shown in Column Two opposite the corresponding axle group spacing shown in Column One of Table 3 (Act), page 23.





2) Three Axle Group

Means three consecutive axles, not including the front axle of a motor vehicle,

- (i) that do not form a triple axle
- (ii) that are entirely within either a motor vehicle or trailer or semi-trailer,
- (iii) in which the spacings between the consecutive axles do not exceed 2.5 metres, and
- (iv) which are not included in a four axle group.

The maximum weight for a three axle group shall not exceed that weight shown in Column Two opposite the corresponding axle group spacing shown in Column One of Table 4 (Act), page 23.




3) Four Axle Group

Means four consecutive axles, not including the front axle of a motor vehicle,

- (i) that are entirely within either a motor vehicle or trailer or semi-trailer, and
- (ii) in which the spacings between the consecutive axles do not exceed 2.5 metres.

The maximum weight for a four axle group shall not exceed that weight shown in Column Two opposite the corresponding axle group spacing shown in Column One of Table 5 (Act), page 24.



CALCULATION OF MAXIMUM ALLOWABLE

GROSS VEHICLE WEIGHTS

The following definitions (contained in Regulation 597 apply to the determination of allowable gross weights.

Base Length	Means the distance measured between the centres of the first axle of the front axle of a vehicle or combination of vehicles and the last axle of a vehicle or combination of vehicles (see example A).
-------------	--

Front Axle Weight	Means, <ul style="list-style-type: none">(i) for a single front axle, that part of the gross vehicle weight transmitted to the highway by the front axle.(ii) for a dual front axle, one-half of that part of the gross vehicle weight transmitted to the highway by the front axle, and(iii) for a triple front axle, one-third of that part of the gross vehicle weight transmitted to the highway by the front axle.
-------------------	---


Inter-Vehicle
Unit Distance

For a combination of vehicles means,

- (i) the distance measured between the centres of the last axle of the tractor and the first trailer or semi-trailer or,
- (ii) the distance measured between the centres of the last axle of the first trailer or semi-trailer and the first axle of the second trailer or semi-trailer,


whichever is smaller (see example B).

Example A.



"d" = Inter-Vehicle-Unit Distance

Example B.



d_2 = Inter-Vehicle-Unit Distance


(d_2 is smaller than d_1)

Intra-Vehicle Unit Distance

For a five or six axle vehicle without trailer or semi-trailer means,

- (i) the distance measured between the centres of the second and the third axles from the front of the vehicle,
- (ii) the distance measured between the centres of the third and the fourth axles from the front of the vehicle,

whichever is greater (see Example C).



d_1 = Inter-Vehicle-Unit Distance
(d_1 is larger than d_2)

Number of Axles

Means the total number of axles on a vehicle or combination of vehicles which are transmitting weight to the highway.

To calculate the maximum allowable gross vehicle weight, the following procedure should be followed:

- (a) Establish actual front axle weight. If the weight to be carried on front axle is unknown, a realistic figure should be assumed.
- (b) Count the total number of axles.
- (c) Establish the axle units, (single-dual-triple).
- (d) Measure all inter-axle spacings.
- (e) Establish all inter or intra-vehicle-unit distances.

NOTE: No inter or intra-vehicle-unit distance for vehicles with less than 5 axles.

- (f) Determine the base length.
- (g) Establish the two, three or four axle groups, if any.

When the above data has been collected a maximum of three calculations should be made. The allowable gross weight for a vehicle or combination of vehicles will be the least of the three calculations.

Calculation 1

Front axle weight plus the maximum allowable weight for all axle units from Tables 1 and 2. (Act), page 22.

Calculation 2

(Only if a two, three, or four axle group is present).

Front axle weight plus the maximum allowable weights for any two, three, or four axle group plus the maximum allowable weight for any axle unit or units which are not part of any axle group.


Calculation 3

That weight prescribed in Regulation 597 (Tables 1-29) having consideration to:

- (a) Number of axles
- (b) Inter or intra-vehicle-unit distance
- (c) Front axle weight
- (d) Base Length

NOTE: An axle unit, within an axle group, may weigh that weight allowed by the axle unit Tables (1 and 2 - Act) if the allowable axle group weight is not exceeded.

Example 1



Base Length	=	4.60 m (3.05 + 1.55)
Inter-Vehicle-Unit Distance Actual (or estimated)	=	Not applicable
Front axle weight	=	7 500 kg

Calculation 1

7 500 + 17 900 = 25 400 kg*

Calculation 2


Not applicable, no axle groups present

Calculation 3

Table 1 (Reg) = 26 300 kg

*Maximum allowable gross vehicle weight is the least of the three calculations = 25 400 kg

Example 2



Base Length	=	7.24 m
Inter-Vehicle-Unit Distance	=	3.04 m
Actual (or estimated) front axle weight	=	4 650 kg

Calculation 1

$$4\,650 + 10\,000 + 17\,500 = 32\,150 \text{ kg}^*$$

Calculation 2


Not applicable, no axle
groups present

Calculation 3

$$\text{Table 2 (Reg)} = 33\,000 \text{ kg}$$

*Maximum allowable gross
vehicle weight is the least
of the three calculations = 32 150 kg

Example 3



Base Length	=	9.13 m
Inter-Vehicle-Unit Distance	=	3.81 m
Actual (or estimated) front axle weight	=	5 200 kg

Calculation 1

$$5\,200 + 17\,000 + 19\,100 = 41\,300 \text{ kg}$$

Calculation 2

Not applicable, no axle groups present


Calculation 3

$$\text{Table 8 (Reg)} = 39\,400 \text{ kg}^*$$

*Maximum allowable gross weight is the least of the three calculations

$$= 39\,400 \text{ kg}$$

Example 4



Base Length	=	10.25 m
Inter-Vehicle-Unit Distance	=	3.85 m
Actual (or estimated) front axle weight	=	4 980 kg

Calculation 1

$$4\,980 + 17\,000 + 10\,000 + 10\,000 = 41\,980 \text{ kg}$$

Calculation 2

$$4\,980 + 17\,000 + 18\,600 = 40\,580 \text{ kg}^*$$


Calculation 3

$$\text{Table 8 (Reg)} = 40\,700 \text{ kg}$$

*Maximum allowable gross vehicle weight is the least of the three calculations

$$= 40\,580 \text{ kg}$$

Example 5



Base Length	=	14.93 m
Inter-Vehicle-Unit Distance	=	5.68 m
Actual (or estimated) front axle weight	=	5 370 kg

Calculation 1

$$5\,370 + 17\,000 + 10\,000 + 19\,100 = 51\,370 \text{ kg}$$

Calculation 2


$$5\,370 + 17\,000 + 26\,000 = 48\,370 \text{ kg}^*$$

Calculation 3

$$\text{Table 15 (Reg)} = 52\,500 \text{ kg}$$

* Maximum allowable gross vehicle weight is the least of the three calculations = 48 370 kg

Example 6



Base Length	=	13.32 m
Inter-Vehicle-Unit Distance	=	3.37 m
Actual (or estimated) front axle weight	=	5 120 kg

Calculation 1

$$\begin{aligned}
 &5\,120 + 17\,900 + 10\,000 \\
 &+ 10\,000 + 17\,000 \quad = \quad 60\,020 \text{ kg}
 \end{aligned}$$

Calculation 2

$$5\,120 + 17\,900 + 28\,900 = 51\,920 \text{ kg}^*$$


Calculation 3

$$\text{Table 21 (Reg)} = 52\,000 \text{ kg}$$

*Maximum allowable gross vehicle weight is the least of the three calculations

$$= 51\,920 \text{ kg}$$

Example 7



Base Length	=	20.10 m
Inter-Vehicle-Unit Distance	=	2.95 m
Actual (or estimated) front axle weight	=	4 760 kg

Calculation 1

$$\begin{aligned}
 &4\,760 + 17\,500 + 10\,000 \\
 &+ 17\,000 + 10\,000 + 17\,200 = 76\,460 \text{ kg}
 \end{aligned}$$

Calculation 2

Not applicable, no axle groups present

Calculation 3

$$\text{Table 26 (Reg)} = 58\,800 \text{ kg}^*$$

*Maximum allowable gross vehicle weight is the least of the three calculations

$$= 58\,800 \text{ kg}$$

TABLE 1 (ACT)
MAXIMUM ALLOWABLE WEIGHT FOR
DUAL AXLE

COLUMN ONE	COLUMN TWO
Axle Spacing (Metres)	Maximum Allowable Weight (Kilogram)
1.0 to less than 1.2	15,400
1.2 to less than 1.3	17,000
1.3 to less than 1.4	17,200
1.4 to less than 1.5	17,500
1.5 to less than 1.6	17,900
1.6 to less than 1.7	18,300
1.7 to less than 1.8	18,700
1.8 or more	19,100

TABLE 2 (ACT)
MAXIMUM ALLOWABLE WEIGHT FOR
TRIPLE AXLE

COLUMN ONE	COLUMN TWO
Axle Spacing (Metres)	Maximum Allowable Weight (Kilograms)
2.0 to less than 2.4	19,500
2.4 to less than 2.8	21,300
2.8 to less than 2.9	21,700
2.9 to less than 3.0	22,000
3.0 to less than 3.2	23,000
3.2 to less than 3.3	23,100
3.3 to less than 3.4	23,400
3.4 to less than 3.5	23,800
3.5 to less than 3.6	24,100
3.6 to less than 3.7	24,400
3.7 to less than 3.8	24,800
3.8 to less than 3.9	25,100
3.9 to less than 4.0	25,500
4.0 to less than 4.1	25,800
4.1 to less than 4.2	26,200
4.2 to less than 4.3	26,500
4.3 to less than 4.4	26,900
4.4 to less than 4.5	27,200
4.5 to less than 4.6	27,600
4.6 to less than 4.7	27,900
4.7 to less than 4.8	28,300
4.8 or more	28,600

TABLE 3 (ACT)
MAXIMUM ALLOWABLE WEIGHT FOR
TWO AXLE GROUP

COLUMN ONE	COLUMN TWO
Axle Group Spacing (Metres)	Maximum Allowable Weight (Kilograms)
1.0 to less than 1.2	15,000
1.2 to less than 1.3	16,300
1.3 to less than 1.4	16,700
1.4 to less than 1.5	17,000
1.5 to less than 1.6	17,400
1.6 to less than 1.7	17,800
1.7 to less than 1.8	18,200
1.8 to less than 1.9	18,600
1.9 to less than 2.0	19,100

TABLE 4 (ACT)
MAXIMUM ALLOWABLE WEIGHT FOR
THREE AXLE GROUP

COLUMN ONE	COLUMN TWO
Axle Group Spacing (Metres)	Maximum Allowable Weight (Kilograms)
2.0 to less than 2.4	19,000
2.4 to less than 2.6	20,400
2.6 to less than 2.8	21,000
2.8 to less than 2.9	21,400
2.9 to less than 3.0	21,700
3.0 to less than 3.1	22,000
3.1 to less than 3.2	22,400
3.2 to less than 3.3	22,700
3.3 to less than 3.4	23,000
3.4 to less than 3.5	23,400
3.5 to less than 3.6	23,700
3.6 to less than 3.7	24,000
3.7 to less than 3.8	24,400
3.8 to less than 3.9	24,700
3.9 to less than 4.0	25,000
4.0 to less than 4.1	25,400
4.1 to less than 4.2	25,700
4.2 to less than 4.3	26,000
4.3 to less than 4.4	26,400
4.4 to less than 4.5	26,700
4.5 to less than 4.6	27,000
4.6 to less than 4.7	27,400
4.7 to less than 4.8	27,700
4.8 to less than 4.9	28,000
4.9 to less than 5.0	28,300
5.0 or more	28,600

TABLE 5 (ACT)
MAXIMUM ALLOWABLE WEIGHT FOR
FOUR AXLE GROUP

COLUMN ONE	COLUMN TWO
Axle Group Spacing (Metres)	Maximum Allowable Weight (Kilograms)
Less than 3.6	23,500
3.6 to less than 3.7	23,900
3.7 to less than 3.8	24,200
3.8 to less than 3.9	24,600
3.9 to less than 4.0	24,900
4.0 to less than 4.1	25,300
4.1 to less than 4.2	25,700
4.2 to less than 4.3	26,000
4.3 to less than 4.4	26,400
4.4 to less than 4.5	26,700
4.5 to less than 4.6	27,100
4.6 to less than 4.7	27,500
4.7 to less than 4.8	27,800
4.8 to less than 4.9	28,200
4.9 to less than 5.0	28,500
5.0 to less than 5.1	28,900
5.1 to less than 5.2	29,300
5.2 to less than 5.3	29,600
5.3 to less than 5.4	30,000
5.4 to less than 5.5	30,300
5.5 to less than 5.6	30,700
5.6 to less than 5.7	31,100
5.7 to less than 5.8	31,400
5.8 to less than 5.9	31,800
5.9 to less than 6.0	32,100
6.0 to less than 6.1	32,500
6.1 to less than 6.2	32,900
6.2 to less than 6.3	33,200
6.3 to less than 6.4	33,600
6.4 to less than 6.5	33,900
6.5 to less than 6.6	34,300
6.6 to less than 6.7	34,700
6.7 to less than 6.8	35,000
6.8 to less than 6.9	35,400
6.9 to less than 7.0	35,700
7.0 to less than 7.1	36,100
7.1 to less than 7.2	36,500
7.2 to less than 7.3	36,800
7.3 to less than 7.4	37,200
7.4 to less than 7.5	37,600
7.5 or more	38,000

VEHICLE WEIGHT TABLE 1 (REG)

Allowable Gross Weight On A Vehicle With **Three Axles** (kilograms)
Front Axle Weight (kilograms)

BASE LENGTH, (METRES)	Front Axle Weight (kilograms)							
	5 000 or LESS	5 001 TO LESS THAN 5 500	5 501 TO LESS THAN 6 000	6 001 TO LESS THAN 6 500	6 501 TO LESS THAN 7 000	7 001 TO LESS THAN 7 500	7 501 TO LESS THAN 8 000	8 001 TO LESS THAN 8 500
LESS THAN 4.00	22,600	22,900	23,100	23,400	23,600	23,800	24,000	24,200
4.00 TO LESS THAN 4.10	22,900	23,200	23,400	23,700	23,900	24,100	24,300	24,500
4.10 TO LESS THAN 4.20	23,300	23,600	23,800	24,100	24,300	24,500	24,700	25,000
4.20 TO LESS THAN 4.30	23,600	23,900	24,100	24,400	24,600	24,800	25,000	25,200
4.30 TO LESS THAN 4.40	23,800	24,200	24,400	24,700	24,900	25,100	25,300	25,500
4.40 TO LESS THAN 4.50	23,800	24,300	24,800	25,100	25,300	25,500	25,700	25,900
4.50 TO LESS THAN 4.60	23,800	24,300	24,800	25,300	25,600	25,800	26,000	26,200
4.60 TO LESS THAN 4.70	23,800	24,300	24,800	25,300	25,800	26,100	26,300	26,500
4.70 TO LESS THAN 4.80	23,800	24,300	24,800	25,300	25,800	26,300	26,700	26,900
4.80 TO LESS THAN 4.90	23,800	24,300	24,800	25,300	25,800	26,300	26,800	27,200
4.90 TO LESS THAN 5.00	23,800	24,300	24,800	25,300	25,800	26,300	26,800	27,300
5.00 AND OVER	23,800	24,300	24,800	25,300	25,800	26,300 *	26,800	27,300

9 500 TO
LESS
THAN
10 000

9 000 TO
LESS
THAN
9 500

8 500 TO
LESS
THAN
9 000

8 000 TO
LESS
THAN
8 500

24,400

25,000

25,300

25,700

26,000

26,300

26,700

27,000

27,300

27,700

28,000

28,400

28,800

VEHICLE WEIGHT TABLE 2 (REG)

Allowable Gross Weight On A Vehicle With Four Axles (kilograms)
Front Axle Weight (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
LESS THAN 5.00	28,600	28,900	29,100	29,400	29,600	29,800	30,100	30,300	30,500	30,800	31,000
5.00 TO LESS THAN 5.25	29,100	29,400	29,600	29,900	30,200	30,400	30,700	30,900	31,100	31,400	31,600
5.25 TO LESS THAN 5.50	29,600	29,900	30,100	30,400	30,700	30,900	31,300	31,500	31,700	32,100	32,300
5.50 TO LESS THAN 5.75	30,000	30,400	30,600	31,000	31,300	31,500	31,900	32,100	32,400	32,700	33,000
5.75 TO LESS THAN 6.00	30,500	30,900	31,200	31,500	31,800	32,100	32,400	32,700	33,000	33,300	33,600
6.00 TO LESS THAN 6.25	31,000	31,400	31,700	32,000	32,400	32,700	33,000	33,300	33,600	34,000	34,300
6.25 TO LESS THAN 6.50	31,500	31,900	32,200	32,600	32,900	33,200	33,600	33,900	34,300	34,600	34,900
6.50 TO LESS THAN 6.75	32,000	32,400	32,700	33,100	33,500	33,800	34,200	34,500	34,900	35,200	35,500
6.75 TO LESS THAN 7.00	32,500	32,900	33,200	33,600	34,000	34,400	34,800	35,100	35,500	35,900	36,200
7.00 TO LESS THAN 7.25	33,000	33,400	33,700	34,100	34,600	35,000	35,400	35,700	36,100	36,500	36,900
7.25 TO LESS THAN 7.50	33,300	33,800	34,200	34,600	35,100	35,500	35,900	36,300	36,700	37,200	37,600
7.50 AND OVER	33,300	33,800	34,300	34,800	35,300	35,800	36,300	36,800	37,300	37,800	38,300

VEHICLE WEIGHT TABLE 3 (REG)

Allowable Gross Weight On A Vehicle With Five Axles (kilograms)
Inter-Vehicle-Unit Distance, Less Than 2.4 Meters
(Or Intra-Vehicle-Unit Distance)
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
LESS THAN 7.00	30,200	30,600	31,000	31,300	31,700	32,100	32,500	32,900	33,300	33,700	34,100
7.00 TO LESS THAN 7.25	30,700	31,100	31,500	31,900	32,300	32,700	33,000	33,400	33,800	34,200	34,600
7.25 TO LESS THAN 7.50	31,200	31,600	32,000	32,400	32,800	33,200	33,600	34,000	34,400	34,800	35,200
7.50 TO LESS THAN 7.75	31,700	32,100	32,500	32,900	33,300	33,700	34,100	34,500	34,900	35,300	35,700
7.75 TO LESS THAN 8.00	32,200	32,600	33,000	33,400	33,800	34,200	34,600	35,000	35,400	35,800	36,200
8.00 TO LESS THAN 8.25	32,700	33,100	33,500	33,900	34,300	34,700	35,200	35,600	36,000	36,400	36,800
8.25 TO LESS THAN 8.50	33,200	33,600	34,000	34,400	34,900	35,300	35,700	36,100	36,500	36,900	37,300
8.50 TO LESS THAN 8.75	33,700	34,100	34,500	35,000	35,400	35,800	36,200	36,600	37,000	37,400	37,800
8.75 TO LESS THAN 9.00	34,200	34,600	35,100	35,500	35,900	36,300	36,700	37,100	37,600	38,000	38,400
9.00 TO LESS THAN 9.25	34,700	35,100	35,600	36,000	36,400	36,800	37,300	37,700	38,100	38,500	38,900
9.25 TO LESS THAN 9.50	35,200	35,700	36,100	36,500	36,900	37,400	37,800	38,200	38,600	39,100	39,500
9.50 TO LESS THAN 9.75	35,700	36,200	36,600	37,000	37,400	37,900	38,300	38,700	39,200	39,600	40,000
9.75 TO LESS THAN 10.00	36,200	36,700	37,100	37,500	38,000	38,400	38,800	39,300	39,700	40,100	40,500
10.00 TO LESS THAN 10.25	36,700	37,200	37,600	38,100	38,500	38,900	39,400	39,800	40,200	40,700	41,200
10.25 AND OVER	36,700	37,200	37,700	38,200	38,700	39,200	39,700	40,200	40,700	41,200	41,700

VEHICLE WEIGHT TABLE 4 (REG)

Allowable Gross Weight On A Vehicle With Five Axles (kilograms)
Inter-Vehicle-Unit Distance, **2.4 Meters To Less Than 2.7 Meters**
(Or Intra-Vehicle-Unit Distance)
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
LESS THAN 7.25	31,700	32,100	32,500	32,900	33,200	33,600	34,000	34,400	34,700	35,100	35,500
7.25 TO LESS THAN 7.50	32,200	32,600	33,000	33,400	33,800	34,100	34,500	34,900	35,300	35,600	36,000
7.50 TO LESS THAN 7.75	32,700	33,100	33,500	33,900	34,300	34,700	35,100	35,400	35,800	36,200	36,600
7.75 TO LESS THAN 8.00	33,200	33,600	34,000	34,400	34,800	35,200	35,600	36,000	36,400	36,700	37,100
8.00 TO LESS THAN 8.25	33,700	34,100	34,500	34,900	35,300	35,700	36,100	36,500	36,900	37,300	37,700
8.25 TO LESS THAN 8.50	34,200	34,600	35,000	35,400	35,800	36,200	36,600	37,000	37,400	37,800	38,200
8.50 TO LESS THAN 8.75	34,800	35,200	35,600	36,000	36,400	36,800	37,200	37,600	38,000	38,400	38,800
8.75 TO LESS THAN 9.00	35,300	35,700	36,100	36,500	36,900	37,300	37,700	38,100	38,500	38,900	39,300
9.00 TO LESS THAN 9.25	35,800	36,200	36,600	37,000	37,400	37,800	38,200	38,700	39,100	39,500	39,900
9.25 TO LESS THAN 9.50	36,300	36,700	37,100	37,500	37,900	38,400	38,800	39,200	39,600	40,000	40,400
9.50 TO LESS THAN 9.75	36,800	37,200	37,600	38,000	38,000	38,900	39,300	39,700	40,200	40,600	41,000
9.75 TO LESS THAN 10.00	37,300	37,700	38,100	38,600	39,000	39,400	39,800	40,200	40,600	41,000	41,400
10.00 TO LESS THAN 10.25	37,800	38,200	38,700	39,100	39,500	39,900	40,300	40,700	41,100	41,400	41,800
10.25 TO LESS THAN 10.50	37,800	38,300	38,800	39,300	39,800	40,300	40,700	41,100	41,500	41,900	42,300
10.50 AND OVER	37,800	38,300	38,800	39,300	39,800	40,300	40,800	41,300	41,800	42,300	42,800

VEHICLE WEIGHT TABLE 5

Allowable Gross Weight On A Vehicle With Five Axles (kilograms)
Inter-Vehicle-Unit Distance, 2.7 Metres To Less Than 3.0 Metres
(Or Intra-Vehicle-Unit Distance)
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or Less	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL. 10 000
LESS THAN 7.50	33,600	33,900	34,300	34,600	35,000	35,300	35,700	36,000	36,400	36,700	37,100
7.50 TO LESS THAN 7.75	34,100	34,400	34,800	35,100	35,500	35,800	36,200	36,500	36,900	37,200	37,600
7.75 TO LESS THAN 8.00	34,500	34,900	35,300	35,600	36,000	36,300	36,700	37,100	37,400	37,800	38,200
8.00 TO LESS THAN 8.25	35,000	35,400	35,800	36,100	36,500	36,900	37,200	37,600	37,900	38,300	38,700
8.25 TO LESS THAN 8.50	35,500	35,900	36,300	36,600	37,000	37,400	37,700	38,100	38,500	38,800	39,200
8.50 TO LESS THAN 8.75	36,000	36,400	36,700	37,100	37,500	37,900	38,200	38,600	39,000	39,400	39,700
8.75 TO LESS THAN 9.00	36,400	36,800	37,200	37,600	38,000	38,400	38,800	39,100	39,500	39,900	40,300
9.00 TO LESS THAN 9.25	36,900	37,300	37,700	38,100	38,500	38,900	39,300	39,700	40,000	40,400	40,800
9.25 TO LESS THAN 9.50	37,400	37,800	38,200	38,600	39,000	39,400	39,800	40,200	40,600	41,000	41,400
9.50 TO LESS THAN 9.75	37,900	38,300	38,700	39,100	39,500	39,900	40,300	40,700	41,100	41,500	41,900
9.75 TO LESS THAN 10.00	38,400	38,800	39,200	39,600	40,000	40,400	40,800	41,200	41,600	42,000	42,400
10.00 TO LESS THAN 10.25	38,900	39,300	39,700	40,100	40,500	40,900	41,300	41,700	42,100	42,500	42,900
10.25 TO LESS THAN 10.50	39,100	39,600	40,100	40,600	41,000	41,400	41,800	42,300	42,700	43,100	43,600
10.50 AND OVER	39,100	39,600	40,100	40,600	41,100	41,600	42,100	42,600	43,100	43,600	44,100

VEHICLE WEIGHT TABLE 6

Allowable Gross Weight On A Vehicle With Five Axles (kilograms)
Inter-Vehicle-Unit Distance, **3.0 Metres To Less Than 3.3 Metres**
(Or Intra-Vehicle-Unit Distance)
Front Axle Weight, (kilograms)

BASE LENGTH (METRES)	5,000 or Less	5,0001 TO LESS THAN 5,500	5,500 TO LESS THAN 6,000	6,000 TO LESS THAN 6,500	6,500 TO LESS THAN 7,000	7,000 TO LESS THAN 7,500	7,500 TO LESS THAN 8,000	8,000 TO LESS THAN 8,500	8,500 TO LESS THAN 9,000	9,000 TO LESS THAN 9,500	9,500 TO AND INCL 10,000
LESS THAN 8.00	35,200	30,600	31,000	31,300	31,700	32,100	32,500	32,900	33,300	33,700	34,100
8.00 TO LESS THAN 8.25	35,700	31,100	31,500	31,900	32,300	32,700	33,000	33,400	33,800	34,200	34,600
8.25 TO LESS THAN 8.50	36,200	31,600	32,000	32,400	32,800	33,200	33,600	34,000	34,400	34,800	35,200
8.50 TO LESS THAN 8.75	36,700	32,100	32,500	32,900	33,300	33,700	34,100	34,500	34,900	35,300	35,700
8.75 TO LESS THAN 9.00	37,200	32,600	33,000	33,400	33,800	34,200	34,600	35,000	35,400	35,800	36,200
9.00 TO LESS THAN 9.25	37,700	33,100	33,500	33,900	34,300	34,700	35,200	35,600	36,000	36,400	36,800
9.25 TO LESS THAN 9.50	38,100	33,600	34,000	34,400	34,900	35,300	35,700	36,100	36,500	36,900	37,300
9.50 TO LESS THAN 9.75	38,600	34,100	34,500	35,000	35,400	35,800	36,200	36,600	37,000	37,400	37,800
9.75 TO LESS THAN 10.00	39,100	34,600	35,100	35,500	35,900	36,300	36,700	37,100	37,600	38,000	38,400
10.00 TO LESS THAN 10.25	39,600	40,000	40,400	40,800	41,200	41,600	42,000	42,300	42,700	43,100	43,500
10.25 TO LESS THAN 10.50	40,000	40,500	40,900	41,300	41,700	42,100	42,500	42,900	43,300	43,700	44,100
10.50 TO LESS THAN 10.75	40,300	40,800	41,300	41,800	42,200	42,600	43,000	43,400	43,800	44,200	44,600
10.75 AND OVER	40,300	40,800	41,300	41,800	42,300	42,800	43,300	43,800	44,300	44,800	45,300

VEHICLE WEIGHT TABLE 7 (REG)

Allowable Gross Weight On A Vehicle With Five Axles (kilograms)
Inter-Vehicle-Unit Distance, 3.3 Metres Or More
(Or Intra-Vehicle-Unit Distance)
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500					5 501 TO LESS THAN 6 000					6 001 TO LESS THAN 6 500					6 501 TO LESS THAN 7 000					7 001 TO LESS THAN 7 500					7 501 TO LESS THAN 8 000					8 001 TO LESS THAN 8 500					8 501 TO LESS THAN 9 000					9 001 TO LESS THAN 9 500					9 501 TO LESS THAN 10 000							
LESS THAN 8.50	37,300	37,600					37,900					38,200					38,500					38,800					39,000					39,300					39,600					39,900					40,200							
	37,700	38,000					38,300					38,600					38,900					39,200					39,500					39,800					40,100					40,400					40,700							
	38,100	38,400					38,700					39,000					39,400					39,700					40,000					40,300					40,600					40,900					41,200							
8.50 TO LESS THAN 8.75	38,500	38,800					39,100					39,400					39,700					40,000					40,300					40,600					40,900					41,200					41,500							
	38,900	39,200					39,500					39,800					40,100					40,400					40,700					41,000					41,300					41,600					41,900							
	39,300	39,600					39,900					40,200					40,500					40,800					41,100					41,400					41,700					42,000					42,300							
9.25 TO LESS THAN 9.50	39,700	40,000					40,300					40,600					40,900					41,200					41,500					41,800					42,100					42,400					42,700							
	40,100	40,400					40,700					41,000					41,300					41,600					41,900					42,200					42,500					42,800					43,100							
	40,500	40,800					41,100					41,400					41,700					42,000					42,300					42,600					42,900					43,200					43,500							
9.75 TO LESS THAN 10.00	40,900	41,200					41,500					41,800					42,100					42,400					42,700					43,000					43,300					43,600					43,900							
	41,300	41,600					41,900					42,200					42,500					42,800					43,100					43,400					43,700					44,000					44,300							
	41,700	42,000					42,300					42,600					42,900					43,200					43,500					43,800					44,100					44,400					44,700							
10.00 TO LESS THAN 10.25	42,100	42,400					42,700					43,000					43,300					43,600					43,900					44,200					44,500					44,800					45,100							
	42,500	42,800					43,100					43,400					43,700					44,000					44,300					44,600					44,900					45,200					45,500							
	42,900	43,200					43,500					43,800					44,100					44,400					44,700					45,000					45,300					45,600					45,900							
10.25 TO LESS THAN 10.50	43,300	43,600					43,900					44,200					44,500					44,800					45,100					45,400					45,700					46,000					46,300							
	43,700	44,000					44,300					44,600					44,900					45,200					45,500					45,800					46,100					46,400					46,700							
	44,100	44,400					44,700					45,000					45,300					45,600					45,900					46,200					46,500					46,800					47,100							
10.50 TO LESS THAN 10.75	44,500	44,800					45,100					45,400					45,700					46,000					46,300					46,600					46,900					47,200					47,500							
	44,900	45,200					45,500					45,800					46,100					46,400																																

VEHICLE WEIGHT TABLE 8 (REG)

Allowable Gross Weight On A Vehicle With Five Axles (kilograms)
Inter-Vehicle-Unit Distance, **3.6 Metres Or More**
(Or Intra-Vehicle-Unit Distance)
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	Front Axle Weight, (kilograms)									
	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500 AND INCL 10 000
LESS THAN 8.50										
8.50 TO LESS THAN 8.75	38,200	38,400	38,700	38,900	39,200	39,400	39,700	39,900	40,200	40,700
8.75 TO LESS THAN 9.00	38,500	38,800	39,000	39,300	39,600	39,800	40,100	40,400	40,700	41,200
	38,800	39,100	39,400	39,700	40,000	40,300	40,600	40,900	41,200	41,700
9.00 TO LESS THAN 9.25	39,100	39,400	39,700	40,000	40,400	40,700	41,000	41,300	41,600	42,200
9.25 TO LESS THAN 9.50	39,400	39,800	40,100	40,400	40,800	41,100	41,500	41,800	42,100	42,700
9.50 TO LESS THAN 9.75	39,700	40,100	40,400	40,800	41,200	41,600	41,900	42,200	42,600	43,200
9.75 TO LESS THAN 10.00	40,000	40,400	40,800	41,200	41,600	42,000	42,400	42,700	43,100	43,800
10.00 TO LESS THAN 10.25	40,400	40,800	41,200	41,600	42,000	42,400	42,800	43,200	43,600	44,300
10.25 TO LESS THAN 10.50	40,700	41,100	41,500	42,000	42,400	42,800	43,200	43,600	44,000	44,800
10.50 TO LESS THAN 10.75	41,000	41,400	41,800	42,400	42,800	43,200	43,700	44,100	44,500	45,300
10.75 TO LESS THAN 11.00	41,400	41,800	42,200	42,700	43,200	43,700	44,100	44,600	45,000	45,900
11.00 TO LESS THAN 11.25	41,700	42,200	42,600	43,100	43,600	44,100	44,500	45,000	45,500	46,500
11.25 TO LESS THAN 11.50	42,000	42,500	43,000	43,500	44,000	44,500	45,000	45,500	46,000	47,000
11.50 TO LESS THAN 11.75	42,500	43,000	43,500	44,000	44,500	45,000	45,500	46,000	46,500	47,500
11.75 AND OVER	43,000	43,500	44,000	44,500	45,000	45,500	46,000	46,500	47,000	48,000

VEHICLE WEIGHT TABLE 9 (REG)

Allowable Gross Weight On A Vehicle With Six Axles (kilograms)
Inter-Vehicle-Unit Distance, **Less Than 2.1 Metres**
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
9.50 TO LESS THAN 9.75 9.75 TO LESS THAN 10.00	35,800	36,100	36,400	36,800	37,100	37,400	37,700	38,100	38,400	38,700	39,000
	36,400	36,700	37,000	37,300	37,600	38,000	38,300	38,900	39,300	39,600	39,600
	36,900	37,200	37,600	37,900	38,200	38,500	38,900	39,200	39,500	39,800	40,200
10.00 TO LESS THAN 10.25 10.25 TO LESS THAN 10.50 10.50 TO LESS THAN 10.75 10.75 TO LESS THAN 11.00	37,500	37,800	38,100	38,400	38,800	39,100	39,400	39,700	40,100	40,400	40,800
	38,000	38,400	38,700	39,000	39,300	39,700	40,000	40,300	40,600	41,000	41,300
	38,600	38,900	39,200	39,600	39,900	40,200	40,500	40,900	41,200	41,500	41,800
	39,100	39,500	39,800	40,100	40,500	40,800	41,100	41,400	41,800	42,100	42,400
	39,700	40,000	40,400	40,700	41,000	41,300	41,700	42,000	42,300	42,700	43,000
11.00 TO LESS THAN 11.25 11.25 TO LESS THAN 11.50 11.50 TO LESS THAN 11.75 11.75 TO LESS THAN 12.00	40,300	40,600	40,900	41,300	41,600	41,900	42,200	42,600	42,900	43,200	43,500
	40,800	41,200	41,500	41,800	42,100	42,500	42,800	43,100	43,500	43,800	44,100
	41,400	41,700	42,000	42,400	42,700	43,000	43,400	43,700	44,000	44,400	44,700
	41,900	42,300	42,600	42,900	43,300	43,600	43,900	44,300	44,600	44,900	45,300
	42,500	42,800	43,200	43,500	43,800	44,200	44,500	44,800	45,200	45,500	45,800
12.00 TO LESS THAN 12.25 12.25 TO LESS THAN 12.50 12.50 TO LESS THAN 12.75 12.75 TO LESS THAN 13.00	43,100	43,400	43,700	44,100	44,400	44,700	45,100	45,400	45,700	46,000	46,400
	43,600	44,000	44,300	44,600	45,000	45,300	45,600	45,900	46,300	46,600	46,900
	44,200	44,500	44,800	45,200	45,500	45,800	46,200	46,500	46,800	47,200	47,500
	44,700	45,100	45,400	45,700	46,100	46,400	46,700	47,100	47,400	47,700	48,000
	45,300	45,600	46,000	46,300	46,600	47,000	47,300	47,600	48,000	48,300	48,600
13.00 TO LESS THAN 13.25 13.25 TO LESS THAN 13.50 13.50 TO LESS THAN 13.75 13.75 TO LESS THAN 14.00	45,900	46,200	46,500	46,900	47,200	47,500	47,900	48,200	48,500	48,900	49,200
	46,400	46,800	47,100	47,400	47,800	48,100	48,400	48,800	49,100	49,400	49,700
	47,000	47,300	47,600	48,000	48,300	48,700	49,000	49,300	49,700	50,000	50,300
	47,500	47,900	48,200	48,500	48,900	49,200	49,600	49,900	50,200	50,600	50,900
	48,200	48,500	48,800	49,200	49,500	49,800	50,200	50,500	50,900	51,200	51,500
14.00 TO LESS THAN 14.25 14.25 TO LESS THAN 14.50 14.50 TO LESS THAN 14.75 14.75 TO LESS THAN 15.00 15.00 AND OVER	48,500	49,000	49,300	49,700	50,000	50,300	50,700	51,000	51,400	51,700	52,000

VEHICLE WEIGHT TABLE 10 (REG)

Allowable Gross Weight On A Vehicle With Six Axles (kilograms)
Inter-Vehicle-Unit Distance, 2.1 Metres To Less Than 2.4 Metres

Front Axles Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 501 TO LESS THAN 6 000	6 001 TO LESS THAN 6 500	6 501 TO LESS THAN 7 000	7 001 TO LESS THAN 7 500	7 501 TO LESS THAN 8 000	8 001 TO LESS THAN 8 500	8 501 TO LESS THAN 9 000	9 001 TO LESS THAN 9 500	9 501 AND INCL 10 000
LESS THAN 9.50	37,000	37,300	37,600	37,900	38,200	38,500	38,900	39,200	39,500	39,800	40,100
9.50 TO LESS THAN 9.75	37,500	37,800	38,100	38,500	38,800	39,100	39,400	39,700	40,000	40,300	40,700
9.75 TO LESS THAN 10.00	38,100	38,400	38,700	39,000	39,300	39,600	40,000	40,300	40,600	40,900	41,200
10.00 TO LESS THAN 10.25	38,600	38,900	39,200	39,600	39,900	40,200	40,500	40,800	41,200	41,500	41,800
10.25 TO LESS THAN 10.50	39,200	39,500	39,800	40,100	40,400	40,800	41,100	41,400	41,700	42,000	42,300
10.50 TO LESS THAN 10.75	39,700	40,000	40,400	40,700	41,000	41,300	41,600	41,900	42,300	42,600	42,900
10.75 TO LESS THAN 11.00	40,300	40,600	40,900	41,200	41,500	41,900	42,200	42,500	42,800	43,100	43,400
11.00 TO LESS THAN 11.25	40,800	41,100	41,500	41,800	42,100	42,400	42,700	43,100	43,400	43,700	44,100
11.25 TO LESS THAN 11.50	41,400	41,700	42,000	42,300	42,600	43,000	43,300	43,600	43,900	44,300	44,600
11.50 TO LESS THAN 11.75	41,900	42,200	42,600	42,900	43,200	43,500	43,800	44,200	44,500	44,800	45,100
11.75 TO LESS THAN 12.00	42,500	42,800	43,100	43,400	43,800	44,100	44,400	44,700	45,000	45,400	45,700
12.00 TO LESS THAN 12.25	43,000	43,300	43,700	44,000	44,300	44,600	45,000	45,300	45,600	45,900	46,200
12.25 TO LESS THAN 12.50	43,600	43,900	44,200	44,500	44,900	45,200	45,500	45,800	46,200	46,500	46,800
12.50 TO LESS THAN 12.75	44,100	44,400	44,800	45,100	45,400	45,700	46,100	46,400	46,700	47,000	47,300
12.75 TO LESS THAN 13.00	44,700	45,000	45,300	45,600	46,000	46,300	46,600	46,900	47,300	47,600	47,900
13.00 TO LESS THAN 13.25	45,200	45,500	45,900	46,200	46,500	46,800	47,200	47,500	47,800	48,100	48,400
13.25 TO LESS THAN 13.50	45,800	46,100	46,400	46,700	47,100	47,400	47,700	48,100	48,400	48,700	49,000
13.50 TO LESS THAN 13.75	46,300	46,600	47,000	47,300	47,600	48,000	48,300	48,600	48,900	49,300	49,600
13.75 TO LESS THAN 14.00	46,900	47,200	47,500	47,900	48,200	48,500	48,800	49,200	49,500	49,800	50,200
14.00 TO LESS THAN 14.25	47,400	47,700	48,100	48,400	48,700	49,100	49,400	49,700	50,000	50,400	50,700
14.25 TO LESS THAN 14.50	48,000	48,300	48,600	49,000	49,300	49,600	49,900	50,300	50,600	50,900	51,300
14.50 TO LESS THAN 14.75	48,500	48,900	49,200	49,500	49,800	50,200	50,500	50,800	51,200	51,500	51,800
14.75 TO LESS THAN 15.00	49,100	49,400	49,700	50,100	50,400	50,700	51,100	51,400	51,700	52,000	52,400
15.00 AND OVER	49,400	49,900	50,300	50,700	51,000	51,300	51,600	52,000	52,300	52,600	53,000

VEHICLE WEIGHT TABLE 11 (REG)

Allowable Gross Weight On A Vehicle With Six Axles (kilograms)
Inter-Vehicle-Unit Distance, **2.4 Metres To Less Than 2.7 Metres**

Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
LESS THAN 9.50	37,900	38,200	38,500	38,700	39,000	39,300	39,600	39,900	40,200	40,500	40,700
9.50 TO LESS THAN 9.75	38,400	38,700	39,000	39,300	39,600	39,900	40,200	40,500	40,800	41,100	41,400
9.75 TO LESS THAN 10.00	39,000	39,300	39,600	39,900	40,100	40,400	40,700	41,000	41,300	41,600	41,900
10.00 TO LESS THAN 10.25	39,500	39,800	40,100	40,400	40,700	41,000	41,300	41,600	41,900	42,200	42,500
10.25 TO LESS THAN 10.50	40,100	40,400	40,700	41,000	41,300	41,600	41,900	42,200	42,500	42,800	43,100
10.50 TO LESS THAN 10.75	40,600	40,900	41,200	41,500	41,800	42,100	42,400	42,700	43,000	43,300	43,600
10.75 TO LESS THAN 11.00	41,200	41,500	41,800	42,100	42,400	42,700	43,000	43,300	43,600	43,900	44,200
11.00 TO LESS THAN 11.25	41,700	42,000	42,300	42,600	42,900	43,200	43,500	43,800	44,200	44,500	44,800
11.25 TO LESS THAN 11.50	42,200	42,600	42,900	43,200	43,500	43,800	44,100	44,400	44,700	45,000	45,300
11.50 TO LESS THAN 11.75	42,800	43,100	43,400	43,700	44,000	44,300	44,700	45,000	45,300	45,600	45,900
11.75 TO LESS THAN 12.00	43,300	43,700	44,000	44,300	44,600	44,900	45,200	45,500	45,800	46,200	46,500
12.00 TO LESS THAN 12.25	43,900	44,200	44,500	44,800	45,100	45,500	45,800	46,100	46,400	46,700	47,100
12.25 TO LESS THAN 12.50	44,400	44,800	45,100	45,400	45,700	46,000	46,300	46,600	47,000	47,300	47,600
12.50 TO LESS THAN 12.75	45,000	45,300	45,600	45,900	46,300	46,600	46,900	47,200	47,500	47,800	48,100
12.75 TO LESS THAN 13.00	45,500	45,800	46,200	46,500	46,800	47,100	47,500	47,800	48,100	48,400	48,700
13.00 TO LESS THAN 13.25	46,100	46,400	46,700	47,000	47,400	47,700	48,000	48,300	48,700	49,000	49,400
13.25 TO LESS THAN 13.50	46,600	46,900	47,300	47,600	47,900	48,200	48,600	48,900	49,200	49,500	49,800
13.50 TO LESS THAN 13.75	47,200	47,500	47,800	48,200	48,500	48,800	49,100	49,500	49,800	50,100	50,500
13.75 TO LESS THAN 14.00	47,700	48,000	48,400	48,700	49,000	49,400	49,700	50,000	50,300	50,700	51,000
14.00 TO LESS THAN 14.25	48,300	48,600	48,900	49,300	49,600	49,900	50,200	50,600	50,900	51,200	51,600
14.25 TO LESS THAN 14.50	48,800	49,100	49,500	49,800	50,100	50,500	50,800	51,100	51,500	51,800	52,100
14.50 TO LESS THAN 14.75	49,400	49,700	50,000	50,400	50,700	51,000	51,400	51,700	52,000	52,400	52,700
14.75 TO LESS THAN 15.00	49,900	50,200	50,600	50,900	51,300	51,600	51,900	52,300	52,600	52,900	53,300
15.00 AND OVER	50,300	50,800	51,200	51,500	51,800	52,200	52,500	52,800	53,200	53,500	53,800

VEHICLE WEIGHT TABLE 12 (REG)

Allowable Gross Weight On A Vehicle With Six Axles (kilograms)
Inter-Vehicle-Unit Distance, 2.7 Metres To Less Than 3.0 Metres
Front Axle Weight (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
LESS THAN 9.50	38,500	38,800	39,100	39,400	39,700	40,000	40,200	40,500	40,800	41,100	41,400
9.50 TO LESS THAN 9.75	39,100	39,400	39,700	39,900	40,200	40,500	40,800	41,100	41,400	41,700	41,900
9.75 TO LESS THAN 10.00	39,600	39,900	40,200	40,500	40,800	41,100	41,400	41,700	42,000	42,200	42,500
10.00 TO LESS THAN 10.25	40,200	40,500	40,800	41,100	41,400	41,600	41,900	42,200	42,500	42,800	43,100
10.25 TO LESS THAN 10.50	40,700	41,000	41,300	41,600	41,900	42,200	42,500	42,800	43,100	43,400	43,700
10.50 TO LESS THAN 10.75	41,300	41,600	41,900	42,200	42,500	42,800	43,100	43,400	43,700	43,900	44,200
10.75 TO LESS THAN 11.00	41,800	42,100	42,400	42,700	43,000	43,300	43,600	43,900	44,200	44,500	44,800
11.00 TO LESS THAN 11.25	42,400	42,700	43,000	43,300	43,600	43,900	44,200	44,500	44,800	45,100	45,400
11.25 TO LESS THAN 11.50	43,000	43,300	43,600	43,900	44,200	44,500	44,800	45,100	45,400	45,700	46,000
11.50 TO LESS THAN 11.75	43,500	43,800	44,100	44,400	44,700	45,000	45,300	45,600	45,900	46,200	46,500
11.75 TO LESS THAN 12.00	44,100	44,400	44,700	45,000	45,300	45,600	45,900	46,200	46,500	46,800	47,100
12.00 TO LESS THAN 12.25	44,600	44,900	45,200	45,500	45,800	46,100	46,400	46,800	47,100	47,400	47,800
12.25 TO LESS THAN 12.50	45,200	45,500	45,800	46,100	46,400	46,700	47,000	47,300	47,600	47,900	48,200
12.50 TO LESS THAN 12.75	45,700	46,000	46,300	46,600	46,900	47,200	47,500	47,900	48,200	48,500	48,800
12.75 TO LESS THAN 13.00	46,300	46,600	46,900	47,200	47,500	47,800	48,100	48,400	48,800	49,100	49,400
13.00 TO LESS THAN 13.25	46,800	47,100	47,400	47,800	48,100	48,400	48,700	49,000	49,300	49,600	49,900
13.25 TO LESS THAN 13.50	47,400	47,700	48,000	48,300	48,600	48,900	49,200	49,600	49,900	50,200	50,500
13.50 TO LESS THAN 13.75	47,900	48,200	48,500	48,800	49,100	49,400	49,700	50,100	50,500	50,800	51,100
13.75 TO LESS THAN 14.00	48,500	48,800	49,100	49,400	49,700	50,100	50,400	50,700	51,000	51,400	51,700
14.00 TO LESS THAN 14.25	49,000	49,300	49,700	50,000	50,300	50,600	51,000	51,300	51,600	51,900	52,300
14.25 TO LESS THAN 14.50	49,600	49,900	50,200	50,500	50,900	51,200	51,500	51,800	52,200	52,500	52,800
14.50 TO LESS THAN 14.75	50,100	50,400	50,800	51,100	51,400	51,800	52,100	52,400	52,700	53,100	53,400
14.75 TO LESS THAN 15.00	50,700	51,000	51,300	51,700	52,000	52,300	52,600	53,000	53,300	53,600	54,000
15.00 AND OVER	51,200	51,500	51,800	52,200	52,500	52,800	53,200	53,500	53,900	54,200	54,500

VEHICLE WEIGHT TABLE 13 (REG)

Allowable Gross Weight On A Vehicle With Six Axles (kilograms)
Inter-Vehicle-Unit Distance, 3.0 Metres To Less Than 3.3 Metres

Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	Front Axle Weight, (kilograms)									
	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500
LESS THAN 9.50 9.50 TO LESS THAN 9.75 9.75 TO LESS THAN 10.00	39,200	39,500	39,700	40,000	40,300	40,600	40,900	41,200	41,500	41,800
	39,700	40,000	40,300	40,600	40,900	41,200	41,500	41,800	42,100	42,400
	40,300	40,600	40,800	41,100	41,400	41,700	42,000	42,300	42,600	42,900
10.00 TO LESS THAN 10.25 10.25 TO LESS THAN 10.50 10.50 TO LESS THAN 10.75 10.75 TO LESS THAN 11.00	40,800	41,100	41,400	41,700	42,000	42,300	42,600	42,900	43,200	43,500
	41,400	41,700	41,900	42,200	42,500	42,800	43,100	43,400	43,700	44,000
	41,900	42,200	42,500	42,800	43,100	43,400	43,700	44,000	44,300	44,600
	42,400	42,800	43,000	43,300	43,700	44,000	44,300	44,600	44,900	45,200
11.00 TO LESS THAN 11.25 11.25 TO LESS THAN 11.50 11.50 TO LESS THAN 11.75 11.75 TO LESS THAN 12.00	43,000	43,300	43,600	43,900	44,200	44,500	44,900	45,200	45,500	45,800
	43,500	43,900	44,200	44,500	44,800	45,100	45,400	45,700	46,000	46,300
	44,100	44,400	44,700	45,000	45,300	45,600	46,000	46,300	46,600	46,900
	44,600	45,000	45,300	45,600	45,900	46,200	46,600	46,900	47,200	47,500
12.00 TO LESS THAN 12.25 12.25 TO LESS THAN 12.50 12.50 TO LESS THAN 12.75 12.75 TO LESS THAN 13.00	45,200	45,500	45,800	46,100	46,500	46,800	47,100	47,400	47,800	48,100
	45,700	46,100	46,400	46,700	47,000	47,300	47,700	48,000	48,300	48,600
	46,300	46,600	46,900	47,200	47,600	47,900	48,300	48,600	48,900	49,200
	46,800	47,200	47,500	47,800	48,100	48,400	48,800	49,100	49,500	49,800
13.00 TO LESS THAN 13.25 13.25 TO LESS THAN 13.50 13.50 TO LESS THAN 13.75 13.75 TO LESS THAN 14.00	47,400	47,700	48,100	48,400	48,700	49,000	49,400	49,700	50,000	50,300
	47,900	48,300	48,600	48,900	49,300	49,600	50,000	50,300	50,600	50,900
	48,500	48,800	49,200	49,500	49,800	50,100	50,500	50,800	51,100	51,400
	49,000	49,400	49,700	50,000	50,400	50,700	51,100	51,400	51,700	52,000
14.00 TO LESS THAN 14.25 14.25 TO LESS THAN 14.50 14.50 TO LESS THAN 14.75 14.75 TO LESS THAN 15.00	49,600	49,900	50,300	50,600	50,900	51,200	51,700	52,000	52,300	52,600
	50,100	50,500	50,800	51,100	51,500	51,800	52,200	52,500	52,900	53,200
	50,700	51,000	51,400	51,700	52,100	52,400	52,800	53,100	53,500	53,800
	51,200	51,600	52,000	52,300	52,600	52,900	53,400	53,700	54,100	54,400
15.00 AND OVER	51,700	52,100	52,500	52,800	53,200	53,500	53,900	54,200	54,600	54,900

VEHICLE WEIGHT TABLE 14 (REG)

Allowable Gross Weight On A Vehicle With Six Axles (kilograms)
Inter-Vehicle-Unit Distance, 3.3 Metres To Less Than 3.6 Metres
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	Front Axle Weight, (kilograms)									
	5 000 or LESS 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 AND INCL 10 000
LESS THAN 9.50	39,800	40,100	40,400	40,900	41,200	41,500	41,700	42,000	42,300	42,600
9.50 TO LESS THAN 9.75	40,400	40,600	40,900	41,200	41,500	41,800	42,000	42,600	42,900	43,200
9.75 TO LESS THAN 10.00	40,900	41,200	41,500	41,800	42,000	42,300	42,600	43,200	43,400	43,700
10.00 TO LESS THAN 10.25	41,500	41,800	42,000	42,300	42,600	42,900	43,200	43,700	44,000	44,300
10.25 TO LESS THAN 10.50	42,000	42,300	42,600	42,900	43,200	43,500	43,700	44,000	44,600	44,900
10.50 TO LESS THAN 10.75	42,600	42,900	43,100	43,400	43,700	44,000	44,300	44,600	45,200	45,500
10.75 TO LESS THAN 11.00	43,100	43,400	43,700	44,000	44,300	44,600	44,900	45,200	45,700	46,000
11.00 TO LESS THAN 11.25	43,700	44,000	44,300	44,600	44,900	45,100	45,400	46,000	46,300	46,600
11.25 TO LESS THAN 11.50	44,200	44,500	44,800	45,100	45,400	45,700	46,000	46,600	46,900	47,200
11.50 TO LESS THAN 11.75	44,800	45,100	45,400	45,700	46,000	46,300	46,600	47,200	47,500	47,800
11.75 TO LESS THAN 12.00	45,300	45,600	45,900	46,200	46,500	46,800	47,100	47,700	48,000	48,300
12.00 TO LESS THAN 12.25	45,900	46,200	46,500	46,800	47,100	47,400	48,000	48,300	48,600	48,900
12.25 TO LESS THAN 12.50	46,400	46,700	47,100	47,400	47,700	48,000	48,600	48,900	49,200	49,500
12.50 TO LESS THAN 12.75	47,000	47,300	47,600	47,900	48,200	48,500	49,100	49,500	49,800	50,100
12.75 TO LESS THAN 13.00	47,500	47,900	48,200	48,500	48,800	49,100	49,400	50,000	50,300	50,600
13.00 TO LESS THAN 13.25	48,100	48,400	48,700	49,000	49,300	49,700	50,300	50,600	50,900	51,200
13.25 TO LESS THAN 13.50	48,700	49,000	49,300	49,600	19,900	50,200	50,900	51,200	51,500	51,900
13.50 TO LESS THAN 13.75	49,200	49,500	49,800	50,200	50,500	50,800	51,400	51,700	52,100	52,400
13.75 TO LESS THAN 14.00	49,800	50,100	50,400	50,700	51,000	51,400	52,000	52,300	52,600	52,900
14.00 TO LESS THAN 14.25	50,300	50,600	51,000	51,300	51,600	51,900	52,600	52,900	53,200	53,600
14.25 TO LESS THAN 14.50	50,900	51,200	51,500	51,800	52,200	52,500	53,100	53,500	53,800	54,200
14.50 TO LESS THAN 14.75	51,400	51,700	52,100	52,400	52,700	53,000	53,700	54,000	54,400	54,700
14.75 TO LESS THAN 15.00	52,000	52,300	52,600	53,000	53,300	53,600	54,300	54,600	54,900	55,300
15.00 AND OVER	52,000	51,500	53,000	53,300	53,600	54,000	54,300	55,000	55,300	55,600

VEHICLE WEIGHT TABLE 15 (REG)

Allowable Gross Weight On A Vehicle With Six Axles (kilograms)

Inter-Vehicle-Unit Distance, 3.6 Metres Or More

Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 501 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL. 10 000
9.50 TO LESS THAN 9.75 9.75 TO LESS THAN 10.00	40,400	40,700	40,900	41,200	41,400	41,700	41,900	42,200	42,400	42,700	42,900
	41,000	41,200	41,500	41,700	42,000	42,300	42,500	42,800	43,000	43,300	43,500
	41,500	41,800	42,000	42,300	42,600	42,800	43,100	43,300	43,600	43,900	44,100
10.00 TO LESS THAN 10.25 10.25 TO LESS THAN 10.50 10.50 TO LESS THAN 10.75 10.75 TO LESS THAN 11.00	42,100	42,300	42,600	42,900	43,100	43,400	43,700	43,900	44,200	44,400	44,700
	42,600	42,900	43,200	43,400	43,700	44,000	44,200	44,500	44,800	45,000	45,300
	43,200	43,400	43,700	44,000	44,300	44,500	44,800	45,100	45,300	45,600	45,900
	43,700	44,000	44,300	44,600	44,800	45,100	45,400	45,600	45,900	46,200	46,500
	44,300	44,600	44,800	45,100	45,400	45,700	46,000	46,200	46,500	46,800	47,100
11.00 TO LESS THAN 11.25 11.25 TO LESS THAN 11.50 11.50 TO LESS THAN 11.75 11.75 TO LESS THAN 12.00	44,300	44,600	44,800	45,100	45,400	45,700	46,000	46,200	46,500	46,800	47,100
	44,800	45,100	45,400	45,700	46,000	46,200	46,500	46,800	47,100	47,400	47,700
	45,400	45,700	46,000	46,200	46,500	46,800	47,100	47,400	47,700	48,000	48,200
	45,900	46,200	46,500	46,800	47,100	47,400	47,700	48,000	48,200	48,500	48,800
	46,500	46,800	47,100	47,400	47,700	47,900	48,200	48,500	48,800	49,100	49,400
12.00 TO LESS THAN 12.25 12.25 TO LESS THAN 12.50 12.50 TO LESS THAN 12.75 12.75 TO LESS THAN 13.00	47,000	47,300	47,600	47,900	48,200	48,500	48,800	49,100	49,400	49,700	50,000
	47,600	47,900	48,200	48,500	48,800	49,100	49,400	49,700	50,000	50,300	50,600
	48,200	48,500	48,800	49,100	49,400	49,700	50,000	50,300	50,600	50,900	51,200
	48,700	49,000	49,300	49,600	49,900	50,200	50,500	50,800	51,100	51,400	51,700
	49,300	49,600	49,900	50,200	50,500	50,800	51,100	51,400	51,700	52,000	52,300
13.00 TO LESS THAN 13.25 13.25 TO LESS THAN 13.50 13.50 TO LESS THAN 13.75 13.75 TO LESS THAN 14.00	50,100	50,400	50,700	51,000	51,300	51,600	51,900	52,200	52,500	52,800	53,100
	50,700	51,000	51,300	51,600	51,900	52,200	52,500	52,800	53,100	53,400	53,700
	51,300	51,600	51,900	52,200	52,500	52,800	53,100	53,400	53,700	54,000	54,300
	51,900	52,200	52,500	52,800	53,100	53,400	53,700	54,000	54,300	54,600	54,900
	52,500	52,800	53,100	53,400	53,700	54,000	54,300	54,600	54,900	55,200	55,500
14.00 TO LESS THAN 14.25 14.25 TO LESS THAN 14.50 14.50 TO LESS THAN 14.75 14.75 TO LESS THAN 15.00	53,500	53,800	54,100	54,400	54,700	55,000	55,300	55,600	55,900	56,200	56,500
	54,100	54,400	54,700	55,000	55,300	55,600	55,900	56,200	56,500	56,800	57,100
	54,700	55,000	55,300	55,600	55,900	56,200	56,500	56,800	57,100	57,400	57,700
	55,300	55,600	55,900	56,200	56,500	56,800	57,100	57,400	57,700	58,000	58,300
	55,900	56,200	56,500	56,800	57,100	57,400	57,700	58,000	58,300	58,600	58,900
15.00 AND OVER	52,000	52,500	53,000	53,500	54,000	54,500	55,000	55,300	55,600	56,000	56,300

VEHICLE WEIGHT TABLE 16 (REG)

Allowable Gross Weight On A Vehicle With Seven Axles (kilograms)
Inter-Vehicle-Unit Distance, Less Than 2.1 Metres

Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 AND INCL 10 000
LESS THAN 13.50	45,500	46,000	46,500	47,000	47,500	48,000	48,400	48,900	49,400	49,900	50,400
13.50 TO LESS THAN 13.75	46,000	46,400	46,900	47,400	47,900	48,400	48,800	49,300	49,800	50,300	50,800
13.75 TO LESS THAN 14.00	46,400	46,900	47,300	47,800	48,300	48,800	49,200	49,700	50,200	50,700	51,200
14.00 TO LESS THAN 14.25	46,900	47,300	47,800	48,200	48,700	49,200	49,600	50,100	50,600	51,000	51,500
14.25 TO LESS THAN 14.50	47,400	47,800	48,200	48,600	49,100	49,600	50,000	50,500	51,000	51,400	51,900
14.50 TO LESS THAN 14.75	47,800	48,200	48,600	49,100	49,500	50,000	50,400	50,900	51,300	51,800	52,200
14.75 TO LESS THAN 15.00	48,300	48,600	49,000	49,500	49,900	50,400	50,800	51,300	51,700	52,200	52,600
15.00 TO LESS THAN 15.25	48,700	49,100	49,400	49,900	50,300	50,800	51,200	51,700	52,100	52,600	53,000
15.25 TO LESS THAN 15.50	49,200	49,500	49,900	50,300	50,700	51,200	51,600	52,100	52,500	52,900	53,300
15.50 TO LESS THAN 15.75	49,700	50,000	50,300	50,700	51,100	51,600	52,000	52,500	52,900	53,300	53,700
15.75 TO LESS THAN 16.00	50,100	50,400	50,700	51,100	51,600	52,000	52,400	52,800	53,300	53,700	54,100
16.00 TO LESS THAN 16.25	50,600	50,800	51,100	51,600	52,000	52,400	52,800	53,300	53,700	54,100	54,600
16.25 TO LESS THAN 16.50	51,000	51,300	51,600	52,000	52,400	52,800	53,200	53,700	54,100	54,500	55,000
16.50 TO LESS THAN 16.75	51,400	51,700	52,000	52,400	52,800	53,200	53,700	54,100	54,500	54,900	55,400
16.75 TO LESS THAN 17.00	51,800	52,100	52,400	52,800	53,200	53,700	54,100	54,500	54,900	55,300	55,800
17.00 TO LESS THAN 17.25	52,200	52,500	52,800	53,300	53,700	54,100	54,500	54,900	55,300	55,700	56,200
17.25 TO LESS THAN 17.50	52,700	53,000	53,300	53,700	54,100	54,500	54,900	55,300	55,700	56,200	56,600
17.50 TO LESS THAN 17.75	53,100	53,400	53,700	54,100	54,500	54,900	55,300	55,700	56,200	56,600	57,000
17.75 TO LESS THAN 18.00	53,500	53,800	54,100	54,500	54,900	55,300	55,700	56,200	56,600	57,000	57,400
18.00 TO LESS THAN 18.25	53,900	54,200	54,500	55,000	55,400	55,800	56,200	56,600	57,000	57,400	57,800
18.25 TO LESS THAN 18.50	54,300	54,700	55,000	55,400	55,800	56,200	56,600	57,000	57,400	57,800	58,200
18.50 TO LESS THAN 18.75	54,800	55,100	55,400	55,800	56,200	56,600	57,000	57,400	57,800	58,200	58,600
18.75 TO LESS THAN 19.00	55,200	55,500	55,900	56,200	56,600	57,000	57,400	57,800	58,200	58,600	59,000
19.00 TO LESS THAN 19.25	55,600	55,900	56,300	56,600	57,000	57,400	57,800	58,200	58,600	59,000	59,400
19.25 AND OVER	56,000	56,300	56,700	57,000	57,400	57,800	58,200	58,600	59,000	59,400	59,800

VEHICLE WEIGHT TABLE 17 (REG)

Allowable Gross Weight On A Vehicle With Seven Axles (kilograms)
Inter-Vehicle-Unit Distance, 2.1 Metres To Less Than 2.4 Metres

Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	6 000		6 500		7 000		7 500		8 000		8 500		9 000		9 500	
			TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO LESS THAN	TO AND INCL	TO 10 000
LESS THAN 13.50	46,500	47,000	47,500	47,900	48,400	48,800	49,200	49,600	50,100	50,500	50,900	51,300	51,700	52,100	52,500	53,000	53,400	53,800
13.50 TO LESS THAN 13.75	46,900	47,400	47,900	48,300	48,800	49,200	49,600	50,000	50,400	50,800	51,200	51,600	52,000	52,400	52,800	53,200	53,600	54,000
13.75 TO LESS THAN 14.00	47,300	47,800	48,300	48,700	49,200	49,600	50,000	50,400	50,800	51,200	51,600	52,000	52,400	52,800	53,200	53,600	54,000	54,400
14.00 TO LESS THAN 14.25	47,800	48,200	48,700	49,200	49,600	50,000	50,400	50,800	51,200	51,600	52,000	52,400	52,800	53,200	53,600	54,000	54,400	54,800
14.25 TO LESS THAN 14.50	48,200	48,700	49,100	49,600	50,000	50,400	50,800	51,200	51,600	52,000	52,400	52,800	53,200	53,600	54,000	54,400	54,800	55,200
14.50 TO LESS THAN 14.75	48,600	49,100	49,500	50,000	50,400	50,800	51,200	51,600	52,000	52,400	52,800	53,200	53,600	54,000	54,400	54,800	55,200	55,600
14.75 TO LESS THAN 15.00	49,100	49,500	50,000	50,400	50,800	51,200	51,600	52,000	52,400	52,800	53,200	53,600	54,000	54,400	54,800	55,200	55,600	56,000
15.00 TO LESS THAN 15.25	49,500	49,900	50,400	50,800	51,200	51,600	52,000	52,400	52,800	53,200	53,600	54,000	54,400	54,800	55,200	55,600	56,000	56,400
15.25 TO LESS THAN 15.50	49,900	50,400	50,800	51,200	51,600	52,000	52,400	52,800	53,200	53,600	54,000	54,400	54,800	55,200	55,600	56,000	56,400	56,800
15.50 TO LESS THAN 15.75	50,400	50,800	51,200	51,600	52,000	52,400	52,800	53,200	53,600	54,000	54,400	54,800	55,200	55,600	56,000	56,400	56,800	57,200
15.75 TO LESS THAN 16.00	50,800	51,200	51,600	52,000	52,400	52,800	53,200	53,600	54,000	54,400	54,800	55,200	55,600	56,000	56,400	56,800	57,200	57,600
16.00 TO LESS THAN 16.25	51,300	51,700	52,100	52,500	52,900	53,300	53,700	54,100	54,500	54,900	55,300	55,700	56,100	56,500	56,900	57,300	57,700	58,100
16.25 TO LESS THAN 16.50	51,700	52,100	52,500	52,900	53,300	53,700	54,100	54,500	54,900	55,300	55,700	56,100	56,500	56,900	57,300	57,700	58,100	58,500
16.50 TO LESS THAN 16.75	52,200	52,600	53,000	53,400	53,800	54,200	54,600	55,000	55,400	55,800	56,200	56,600	57,000	57,400	57,800	58,200	58,600	59,000
16.75 TO LESS THAN 17.00	52,600	53,000	53,400	53,800	54,200	54,600	55,000	55,400	55,800	56,200	56,600	57,000	57,400	57,800	58,200	58,600	59,000	59,400
17.00 TO LESS THAN 17.25	53,100	53,500	53,900	54,300	54,700	55,100	55,500	55,900	56,300	56,700	57,100	57,500	57,900	58,300	58,700	59,100	59,500	59,900
17.25 TO LESS THAN 17.50	53,600	53,900	54,300	54,700	55,100	55,500	55,900	56,300	56,700	57,100	57,500	57,900	58,300	58,700	59,100	59,500	59,900	60,300
17.50 TO LESS THAN 17.75	54,000	54,400	54,800	55,200	55,600	56,000	56,400	56,800	57,200	57,600	58,000	58,400	58,800	59,200	59,600	60,000	60,400	60,800
17.75 TO LESS THAN 18.00	54,500	54,900	55,200	55,600	56,000	56,400	56,800	57,200	57,600	58,000	58,400	58,800	59,200	59,600	60,000	60,400	60,800	61,200
18.00 TO LESS THAN 18.25	54,900	55,300	55,700	56,100	56,500	56,900	57,300	57,700	58,100	58,500	58,900	59,300	59,700	60,100	60,500	60,900	61,300	61,700
18.25 TO LESS THAN 18.50	55,400	55,800	56,100	56,500	56,900	57,300	57,700	58,100	58,500	58,900	59,300	59,700	60,100	60,500	60,900	61,300	61,700	62,100
18.50 TO LESS THAN 18.75	55,900	56,200	56,600	57,000	57,400	57,800	58,200	58,600	59,000	59,400	59,800	60,200	60,600	61,000	61,400	61,800	62,200	62,600
18.75 TO LESS THAN 19.00	56,400	56,700	57,000	57,400	57,800	58,200	58,600	59,000	59,400	59,800	60,200	60,600	61,000	61,400	61,800	62,200	62,600	63,000
19.00 TO LESS THAN 19.25	56,900	57,200	57,500	57,800	58,200	58,500	58,800	59,200	59,500	59,900	60,300	60,700	61,100	61,500	61,900	62,300	62,700	63,100
19.25 AND OVER	57,300	57,600	57,900	58,200	58,600	58,900	59,200	59,600	59,900	60,300	60,700	61,100	61,500	61,900	62,300	62,700	63,100	63,500

VEHICLE WEIGHT TABLE 18 (REG)

Allowable Gross Weight On A Vehicle With Seven Axles (kilograms)
Inter-Vehicle-Unit Distance, 2.4 Metres To Less Than 2.7 Metres
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
LESS THAN 13.50	47,300	47,800	48,300	48,800	49,200	49,700	50,100	50,600	51,000	51,500	51,900
13.50 TO LESS THAN 13.75	47,700	48,200	48,700	49,200	49,600	50,100	50,500	51,000	51,400	51,900	52,300
13.75 TO LESS THAN 14.00	48,200	48,600	49,100	49,600	50,000	50,500	50,900	51,400	51,800	52,300	52,700
14.00 TO LESS THAN 14.25	48,600	49,100	49,500	50,000	50,400	50,900	51,300	51,800	52,200	52,700	53,100
14.25 TO LESS THAN 14.50	49,000	49,500	49,900	50,400	50,800	51,300	51,700	52,200	52,600	53,100	53,500
14.50 TO LESS THAN 14.75	49,400	49,900	50,300	50,800	51,200	51,700	52,100	52,600	53,000	53,500	53,900
14.75 TO LESS THAN 15.00	49,900	50,300	50,800	51,200	51,700	52,100	52,600	53,000	53,500	53,900	54,300
15.00 TO LESS THAN 15.25	50,300	50,700	51,200	51,600	52,100	52,500	53,000	53,400	53,900	54,300	54,800
15.25 TO LESS THAN 15.50	50,700	51,100	51,600	52,000	52,500	52,900	53,400	53,800	54,300	54,700	55,200
15.50 TO LESS THAN 15.75	51,100	51,600	52,000	52,400	52,900	53,300	53,800	54,200	54,700	55,100	55,600
15.75 TO LESS THAN 16.00	51,600	52,000	52,400	52,800	53,300	53,700	54,200	54,600	55,100	55,500	56,000
16.00 TO LESS THAN 16.25	52,000	52,400	52,800	53,300	53,700	54,100	54,600	55,000	55,500	55,900	56,400
16.25 TO LESS THAN 16.50	52,500	52,900	53,300	53,700	54,100	54,600	55,000	55,400	55,900	56,300	56,700
16.50 TO LESS THAN 16.75	52,900	53,300	53,700	54,100	54,600	55,000	55,400	55,900	56,300	56,700	57,100
16.75 TO LESS THAN 17.00	53,400	53,700	54,100	54,500	55,000	55,400	55,800	56,300	56,700	57,100	57,500
17.00 TO LESS THAN 17.25	53,800	54,200	54,500	55,000	55,400	55,800	56,300	56,700	57,100	57,500	58,000
17.25 TO LESS THAN 17.50	54,300	54,600	55,000	55,400	55,800	56,200	56,700	57,100	57,500	58,000	58,400
17.50 TO LESS THAN 17.75	54,700	55,000	55,400	55,800	56,200	56,700	57,100	57,500	57,900	58,400	58,800
17.75 TO LESS THAN 18.00	55,200	55,500	55,800	56,200	56,700	57,100	57,500	57,900	58,400	58,800	59,300
18.00 TO LESS THAN 18.25	55,600	55,900	56,200	56,700	57,100	57,500	57,900	58,300	58,800	59,200	59,600
18.25 TO LESS THAN 18.50	56,100	56,400	56,700	57,100	57,500	57,900	58,300	58,800	59,200	59,600	60,000
18.50 TO LESS THAN 18.75	56,500	56,800	57,100	57,500	57,900	58,300	58,800	59,200	59,600	60,000	60,400
18.75 TO LESS THAN 19.00	57,000	57,300	57,500	57,900	58,300	58,800	59,200	59,600	60,000	60,400	60,800
19.00 TO LESS THAN 19.25	57,400	57,700	57,900	58,300	58,800	59,200	59,600	60,000	60,400	60,800	61,200
19.25 AND OVER	57,900	58,100	58,300	58,700	59,200	59,600	60,000	60,400	60,800	61,200	61,600

VEHICLE WEIGHT TABLE 19 (REG)

Allowable Gross Weight On A Vehicle With Seven Axles (kilograms)
Inter-Vehicle-Unit Distance, **2.7 Metres To Less Than 3.0 Metres**
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 AND INCL 10 000
LESS THAN 14.00	48,700	49,200	49,600	50,000	50,500	50,900	51,300	51,700	52,200	52,600	53,000
14.00 TO LESS THAN 14.25	49,200	49,600	50,100	50,500	50,900	51,300	51,800	52,200	52,600	53,000	53,500
14.25 TO LESS THAN 14.50	49,700	50,100	50,500	50,900	51,400	51,800	52,200	52,600	53,100	53,500	53,900
14.50 TO LESS THAN 14.75	50,100	50,600	51,000	51,400	51,800	52,300	52,700	53,100	53,500	53,900	54,300
14.75 TO LESS THAN 15.00	50,600	51,000	51,400	51,900	52,300	52,700	53,100	53,600	54,000	54,400	54,800
15.00 TO LESS THAN 15.25	51,100	51,500	51,900	52,300	52,800	53,200	53,600	54,000	54,400	54,800	55,300
15.25 TO LESS THAN 15.50	51,500	52,000	52,400	52,800	53,200	53,600	54,000	54,500	54,900	55,300	55,700
15.50 TO LESS THAN 15.75	52,000	52,400	52,800	53,300	53,700	54,100	54,500	54,900	55,300	55,700	56,100
15.75 TO LESS THAN 16.00	52,500	52,900	53,300	53,700	54,100	54,500	55,000	55,400	55,800	56,200	56,600
16.00 TO LESS THAN 16.25	52,900	53,300	53,700	54,100	54,500	54,900	55,400	55,800	56,200	56,600	57,000
16.25 TO LESS THAN 16.50	53,300	53,700	54,100	54,500	54,900	55,300	55,800	56,200	56,600	57,000	57,400
16.50 TO LESS THAN 16.75	53,700	54,100	54,500	54,900	55,300	55,700	56,200	56,600	57,000	57,400	57,800
16.75 TO LESS THAN 17.00	54,100	54,500	54,900	55,300	55,700	56,100	56,600	57,000	57,400	57,800	58,200
17.00 TO LESS THAN 17.25	54,600	54,900	55,300	55,700	56,100	56,500	57,000	57,400	57,800	58,200	58,700
17.25 TO LESS THAN 17.50	55,000	55,300	55,600	56,100	56,500	56,900	57,400	57,800	58,200	58,700	59,100
17.50 TO LESS THAN 17.75	55,400	55,700	56,000	56,500	56,900	57,300	57,800	58,200	58,600	59,100	59,500
17.75 TO LESS THAN 18.00	55,800	56,100	56,400	56,900	57,300	57,700	58,200	58,600	59,000	59,500	59,900
18.00 TO LESS THAN 18.25	56,200	56,500	56,800	57,300	57,700	58,100	58,600	59,000	59,400	59,900	60,300
18.25 TO LESS THAN 18.50	56,600	56,900	57,200	57,600	58,100	58,500	59,000	59,400	59,900	60,300	60,700
18.50 TO LESS THAN 18.75	57,100	57,300	57,600	58,000	58,500	58,900	59,400	59,800	60,300	60,700	61,200
18.75 TO LESS THAN 19.00	57,500	57,700	58,000	58,400	58,900	59,300	59,800	60,200	60,700	61,100	61,600
19.00 TO LESS THAN 19.25	57,900	58,100	58,400	58,800	59,300	59,700	60,200	60,600	61,100	61,500	62,000
19.25 AND OVER	58,300	58,500	58,800	59,200	59,700	60,100	60,600	61,000	61,500	61,900	62,400

VEHICLE WEIGHT TABLE 20 (REG)

Allowable Gross Weight On A Vehicle With Seven Axles (kilograms)
Inter-Vehicle-Unit Distance, 3.0 Metres To Less Than 3.3 Metres

Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	Front Axle Weight, (kilograms)									
	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 LESS THAN 6 000	6 000 LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500
LESS THAN 14.00	49,300	49,700	50,200	50,700	51,100	51,600	52,000	52,500	52,900	53,400
14.00 TO LESS THAN 14.25	49,700	50,100	50,600	51,000	51,500	52,000	52,400	52,900	53,400	53,800
14.25 TO LESS THAN 14.50	50,100	50,500	51,000	51,400	51,900	52,400	52,800	53,300	53,800	54,200
14.50 TO LESS THAN 14.75	50,500	51,000	51,400	51,800	52,300	52,800	53,200	53,700	54,200	54,600
14.75 TO LESS THAN 15.00	51,000	51,400	51,700	52,200	52,700	53,200	53,600	54,100	54,600	55,000
15.00 TO LESS THAN 15.25	51,400	51,800	52,100	52,600	53,100	53,600	54,000	54,500	55,000	55,500
15.25 TO LESS THAN 15.50	51,800	52,200	52,500	53,000	53,500	54,000	54,400	54,900	55,400	55,900
15.50 TO LESS THAN 15.75	52,200	52,600	52,900	53,400	53,900	54,400	54,900	55,300	55,800	56,300
15.75 TO LESS THAN 16.00	52,700	53,000	53,300	53,800	54,300	54,800	55,200	55,700	56,200	56,700
16.00 TO LESS THAN 16.25	53,100	53,400	53,700	54,200	54,700	55,200	55,700	56,100	56,600	57,100
16.25 TO LESS THAN 16.50	53,500	53,800	54,100	54,600	55,100	55,600	56,100	56,600	57,000	57,500
16.50 TO LESS THAN 16.75	54,000	54,300	54,600	55,000	55,500	56,000	56,500	57,000	57,400	57,900
16.75 TO LESS THAN 17.00	54,400	54,700	55,000	55,500	56,000	56,400	56,900	57,400	57,900	58,300
17.00 TO LESS THAN 17.25	54,900	55,100	55,400	55,900	56,300	56,800	57,300	57,800	58,300	58,700
17.25 TO LESS THAN 17.50	55,300	55,600	55,800	56,300	56,800	57,200	57,700	58,200	58,700	59,200
17.50 TO LESS THAN 17.75	55,700	56,000	56,200	56,700	57,200	57,700	58,100	58,600	59,100	59,600
17.75 TO LESS THAN 18.00	56,200	56,400	56,600	57,100	57,600	58,100	58,500	59,000	59,500	60,000
18.00 TO LESS THAN 18.25	56,600	56,800	57,100	57,500	58,000	58,500	59,000	59,400	59,900	60,400
18.25 TO LESS THAN 18.50	57,100	57,300	57,500	58,000	58,400	58,900	59,400	59,800	60,300	60,800
18.50 TO LESS THAN 18.75	57,500	57,700	57,900	58,400	58,800	59,300	59,800	60,300	60,700	61,200
18.75 TO LESS THAN 19.00	58,100	58,300	58,500	58,800	59,200	59,600	60,100	60,600	61,000	61,500
19.00 TO LESS THAN 19.25	58,600	58,800	59,000	59,200	59,600	60,000	60,500	61,000	61,400	61,800
19.25 AND OVER	59,000	59,200	59,400	59,600	60,000	60,400	60,900	61,400	61,800	62,200

VEHICLE WEIGHT TABLE 21 (REG)

Allowable Gross Weight On A Vehicle With Seven Axles (kilograms)
Inter-Vehicle-Unit Distance, 3.3 Metres To Less Than 3.6 Metres
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
LESS THAN 15.00	51,600	52,000	52,400	52,800	53,300	53,700	54,200	54,600	55,100	55,500	56,000
15.00 TO LESS THAN 15.25	52,100	52,500	52,800	53,300	53,700	54,200	54,600	55,000	55,500	55,900	56,400
15.25 TO LESS THAN 15.50	52,500	52,900	53,200	53,700	54,100	54,600	55,000	55,500	55,900	56,300	56,800
15.50 TO LESS THAN 15.75	53,000	53,300	53,700	54,100	54,600	55,000	55,400	55,900	56,300	56,800	57,200
15.75 TO LESS THAN 16.00	53,400	53,800	54,100	54,500	55,000	55,400	55,900	56,300	56,800	57,200	57,600
16.00 TO LESS THAN 16.25	53,900	54,200	54,500	55,000	55,400	55,900	56,300	56,700	57,200	57,600	58,000
16.25 TO LESS THAN 16.50	54,300	54,600	54,900	55,400	55,800	56,300	56,700	57,200	57,600	58,000	58,500
16.50 TO LESS THAN 16.75	54,800	55,100	55,400	55,800	56,300	56,700	57,100	57,600	58,000	58,500	59,000
16.75 TO LESS THAN 17.00	55,200	55,500	55,800	56,200	56,700	57,100	57,600	58,000	58,500	59,000	59,400
17.00 TO LESS THAN 17.25	55,600	55,900	56,200	56,700	57,100	57,500	58,000	58,400	58,800	59,300	59,700
17.25 TO LESS THAN 17.50	56,100	56,400	56,700	57,100	57,500	57,900	58,400	58,800	59,200	59,700	60,100
17.50 TO LESS THAN 17.75	56,500	56,800	57,100	57,500	57,900	58,400	58,800	59,200	59,600	60,100	60,400
17.75 TO LESS THAN 18.00	57,000	57,300	57,500	57,900	58,400	58,800	59,200	59,600	60,000	60,400	60,800
18.00 TO LESS THAN 18.25	57,400	57,700	57,900	58,400	58,800	59,200	59,600	60,000	60,400	60,800	61,200
18.25 TO LESS THAN 18.50	57,900	58,100	58,400	58,800	59,200	59,600	60,000	60,400	60,800	61,200	61,600
18.50 TO LESS THAN 18.75	58,300	58,600	58,800	59,200	59,600	60,000	60,400	60,800	61,200	61,600	62,000
18.75 TO LESS THAN 19.00	58,700	59,000	59,300	59,600	60,000	60,400	60,800	61,200	61,600	62,000	62,400
19.00 TO LESS THAN 19.25	59,200	59,500	59,700	60,000	60,400	60,800	61,200	61,600	62,000	62,400	62,800
19.25 AND OVER	59,600	59,900	60,100	60,400	60,800	61,200	61,600	62,000	62,400	62,800	63,200

VEHICLE WEIGHT TABLE 22 (REG)

Allowable Gross Weight On A Vehicle With Seven Axles (kilograms)
Inter-Vehicle-Unit Distance, 3.6 Metres Or More
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 501 TO LESS THAN 6 000	6 001 TO LESS THAN 6 500	6 501 TO LESS THAN 7 000	7 001 TO LESS THAN 7 500	7 501 TO LESS THAN 8 000	8 001 TO LESS THAN 8 500	8 501 TO LESS THAN 9 000	9 001 TO LESS THAN 9 500	9 501 TO AND INCL 10 000
LESS THAN 15.00	52,300	52,700	53,100	53,500	54,000	54,400	54,900	55,300	55,800	56,200	56,700
15.00 TO LESS THAN 15.25	52,800	53,100	53,500	54,000	54,400	54,800	55,300	55,700	56,200	56,600	57,100
15.25 TO LESS THAN 15.50	53,200	53,600	53,900	54,400	54,800	55,300	55,700	56,100	56,600	57,000	57,500
15.50 TO LESS THAN 15.75	53,700	54,000	54,400	54,800	55,200	55,700	56,100	56,500	57,000	57,400	57,900
15.75 TO LESS THAN 16.00	54,100	54,400	54,800	55,200	55,700	56,100	56,500	56,900	57,400	57,800	58,300
16.00 TO LESS THAN 16.25	54,500	54,900	55,200	55,600	56,100	56,500	56,900	57,300	57,800	58,200	58,600
16.25 TO LESS THAN 16.50	55,000	55,300	55,600	56,100	56,500	56,900	57,300	57,800	58,200	58,600	59,000
16.50 TO LESS THAN 16.75	55,400	55,700	56,100	56,500	56,900	57,300	57,700	58,200	58,600	59,000	59,400
16.75 TO LESS THAN 17.00	55,900	56,200	56,500	56,900	57,300	57,700	58,200	58,600	59,000	59,400	59,800
17.00 TO LESS THAN 17.25	56,300	56,600	56,900	57,300	57,700	58,100	58,500	59,000	59,400	59,800	60,300
17.25 TO LESS THAN 17.50	56,700	57,000	57,300	57,700	58,100	58,500	58,900	59,300	59,800	60,200	60,700
17.50 TO LESS THAN 17.75	57,100	57,400	57,700	58,100	58,500	58,900	59,300	59,700	60,100	60,600	61,000
17.75 TO LESS THAN 18.00	57,500	57,800	58,000	58,500	58,900	59,300	59,700	60,100	60,500	60,900	61,300
18.00 TO LESS THAN 18.25	57,900	58,200	58,400	58,800	59,300	59,700	60,100	60,500	60,900	61,300	61,700
18.25 TO LESS THAN 18.50	58,400	58,600	58,800	59,200	59,600	60,100	60,500	60,900	61,300	61,700	62,100
18.50 TO LESS THAN 18.75	58,800	59,000	59,200	59,600	60,000	60,400	60,900	61,300	61,700	62,100	62,500
18.75 TO LESS THAN 19.00	59,300	59,500	59,700	60,000	60,400	60,900	61,300	61,700	62,100	62,500	62,900
19.00 TO LESS THAN 14.25 19.75 AND OVER	59,700 60,100	59,900 60,300	60,200 60,600	60,500 60,900	60,900 61,300	61,300 61,700	61,700 62,100	62,100 62,500	62,500 62,900	62,900 63,300	63,300 63,500

VEHICLE WEIGHT TABLE 23 (REG)

Allowable Gross Weight On A Vehicle With Eight Or More Axles (kilograms)
Inter-Vehicle-Unit Distance, Less Than 2.1 Metres
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 501 TO LESS THAN 6 000	6 001 TO LESS THAN 6 500	6 501 TO LESS THAN 7 000	7 001 TO LESS THAN 7 500	7 501 TO LESS THAN 8 000	8 001 TO LESS THAN 8 500	8 501 TO LESS THAN 9 000	9 001 TO LESS THAN 9 500	9 501 TO LESS THAN 10 000
LESS THAN 15.00	47,600	48,000	48,500	49,000	49,500	50,000	50,400	50,900	51,400	51,900	52,400
15.00 TO LESS THAN 15.25	48,100	48,600	49,000	49,500	50,000	50,500	51,000	51,400	51,900	52,400	52,900
15.25 TO LESS THAN 15.50	48,700	49,100	49,600	50,100	50,500	51,000	51,500	51,900	52,400	52,900	53,400
15.50 TO LESS THAN 15.75	49,200	49,700	50,100	50,600	51,100	51,500	52,000	52,400	52,900	53,400	53,800
15.75 TO LESS THAN 16.00	49,700	50,200	50,700	51,100	51,600	52,000	52,500	52,900	53,400	53,800	54,300
16.00 TO LESS THAN 16.25	50,300	50,700	51,200	51,700	52,100	52,500	53,000	53,400	53,900	54,300	54,800
16.25 TO LESS THAN 16.50	50,800	51,300	51,800	52,200	52,600	53,100	53,500	53,900	54,400	54,800	55,300
16.50 TO LESS THAN 16.75	51,300	51,800	52,300	52,700	53,200	53,600	54,000	54,400	54,900	55,300	55,700
16.75 TO LESS THAN 17.00	51,800	52,300	52,800	53,200	53,600	54,000	54,500	54,900	55,300	55,700	56,100
17.00 TO LESS THAN 17.25	52,300	52,800	53,200	53,700	54,100	54,500	54,900	55,300	55,700	56,100	56,500
17.25 TO LESS THAN 17.50	52,800	53,300	53,700	54,100	54,500	54,900	55,300	55,700	56,100	56,500	57,000
17.50 TO LESS THAN 17.75	53,300	53,800	54,200	54,600	55,000	55,400	55,800	56,200	56,600	57,000	57,400
17.75 TO LESS THAN 18.00	53,800	54,300	54,700	55,100	55,500	55,900	56,200	56,600	57,000	57,400	57,800
18.00 TO LESS THAN 18.25	54,300	54,700	55,100	55,500	55,900	56,300	56,700	57,100	57,500	57,800	58,300
18.25 TO LESS THAN 18.50	54,800	55,200	55,600	56,000	56,400	56,800	57,100	57,500	57,900	58,300	58,800
18.50 TO LESS THAN 18.75	55,300	55,700	56,100	56,500	56,800	57,200	57,600	58,000	58,300	58,700	59,300
18.75 TO LESS THAN 19.00	55,900	56,300	56,700	57,000	57,400	57,700	58,000	58,400	58,800	59,200	59,700
19.00 TO LESS THAN 19.25	56,400	56,800	57,200	57,400	57,800	58,100	58,400	58,800	59,200	59,600	60,100
19.25 AND OVER	56,800	57,200	57,600	57,800	58,200	58,500	58,800	59,200	59,600	60,000	60,500

VEHICLE WEIGHT TABLE 24 (REG)

Allowable Gross Weight On A Vehicle With Eight Or More Axles (kilograms)
Inter-Vehicle-Unit Distance, 2.1 Metres To Less Than 2.4 Metres
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
LESS THAN 15.00	48,600	49,000	49,500	50,000	50,400	50,900	51,400	51,900	52,300	52,800	53,300
15.00 TO LESS THAN 15.25	49,100	49,500	50,000	50,500	50,900	51,400	51,900	52,300	52,800	53,300	53,700
15.25 TO LESS THAN 15.50	49,600	50,100	50,500	51,000	51,400	51,900	52,300	52,800	53,300	53,700	54,200
15.50 TO LESS THAN 15.75	50,100	50,600	51,000	51,500	51,900	52,400	52,800	53,300	53,700	54,200	54,500
15.75 TO LESS THAN 16.00	50,600	51,100	51,600	52,000	52,400	52,900	53,300	53,800	54,200	54,600	55,100
16.00 TO LESS THAN 16.25	51,100	51,600	52,100	52,500	52,900	53,400	53,800	54,200	54,700	55,100	55,500
16.25 TO LESS THAN 16.50	51,700	52,100	52,600	53,000	53,400	53,900	54,300	54,700	55,100	55,500	55,900
16.50 TO LESS THAN 16.75	52,200	52,600	53,100	53,500	53,900	54,300	54,800	55,200	55,600	56,000	56,400
16.75 TO LESS THAN 17.00	52,700	53,200	53,600	54,000	54,400	54,800	55,200	55,600	56,000	56,400	56,800
17.00 TO LESS THAN 17.25	53,200	53,700	54,100	54,500	54,900	55,300	55,700	56,100	56,500	56,900	57,200
17.25 TO LESS THAN 17.50	53,700	54,200	54,600	55,000	55,400	55,800	56,200	56,600	57,000	57,300	57,700
17.50 TO LESS THAN 17.75	54,300	54,700	55,100	55,500	55,900	56,300	56,700	57,000	57,400	57,800	58,200
17.75 TO LESS THAN 18.00	54,800	55,200	55,700	56,000	56,400	56,800	57,100	57,500	57,900	58,200	58,600
18.00 TO LESS THAN 18.25	55,300	55,700	56,200	56,500	56,900	57,300	57,600	58,000	58,300	58,700	59,000
18.25 TO LESS THAN 18.50	55,800	56,300	56,700	57,000	57,400	57,700	58,100	58,400	58,800	59,100	59,500
18.50 TO LESS THAN 18.75	56,400	56,800	57,200	57,500	57,900	58,200	58,600	58,900	59,300	59,600	60,000
18.75 TO LESS THAN 19.00	56,900	57,400	57,800	58,100	58,500	58,800	59,200	59,500	59,900	60,200	60,500
19.00 TO LESS THAN 19.25	57,500	57,900	58,300	58,600	59,000	59,300	59,700	60,000	60,400	60,700	61,000
19.25 AND OVER	57,900	58,300	58,700	59,000	59,400	59,700	60,100	60,400	60,800	61,100	61,400

VEHICLE WEIGHT TABLE 25 (REG)

Allowable Gross Weight On A Vehicle With Eight Or More Axles (kilograms)
Inter-Vehicle-Unit Distance, 2.4 Metres To Less Than 2.7 Metres

Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
LESS THAN 15.00	49,700	50,100	50,600	51,000	51,500	51,900	52,400	52,800	53,300	53,700	54,200
15.00 TO LESS THAN 15.25	50,200	50,600	51,100	51,500	52,000	52,400	52,800	53,300	53,700	54,200	54,600
15.25 TO LESS THAN 15.50	50,700	51,100	51,600	52,000	52,400	52,900	53,300	53,700	54,200	54,600	55,100
15.50 TO LESS THAN 15.75	51,200	51,600	52,100	52,500	52,900	53,300	53,800	54,200	54,600	55,100	55,500
15.75 TO LESS THAN 16.00	51,600	52,100	52,500	53,000	53,400	53,800	54,200	54,700	55,100	55,500	56,000
16.00 TO LESS THAN 16.25	52,100	52,600	53,000	53,500	53,900	54,300	54,700	55,100	55,600	56,000	56,400
16.25 TO LESS THAN 16.50	52,600	53,100	53,500	53,900	54,400	54,800	55,200	55,600	56,000	56,400	56,900
16.50 TO LESS THAN 16.75	53,100	53,500	54,000	54,400	54,800	55,200	55,700	56,100	56,500	56,900	57,300
16.75 TO LESS THAN 17.00	53,600	54,000	54,500	54,900	55,300	55,700	56,100	56,500	56,900	57,300	57,700
17.00 TO LESS THAN 17.25	54,100	54,500	54,900	55,300	55,700	56,200	56,600	57,000	57,400	57,800	58,200
17.25 TO LESS THAN 17.50	54,500	55,000	55,400	55,800	56,200	56,600	57,000	57,400	57,800	58,200	58,600
17.50 TO LESS THAN 17.75	55,000	55,400	55,800	56,300	56,700	57,100	57,500	57,900	58,300	58,700	59,100
17.75 TO LESS THAN 18.00	55,500	55,900	56,300	56,700	57,100	57,500	57,900	58,300	58,700	59,100	59,500
18.00 TO LESS THAN 18.25	56,000	56,400	56,800	57,200	57,600	58,000	58,400	58,800	59,200	59,600	60,000
18.25 TO LESS THAN 18.50	56,500	56,800	57,200	57,600	58,000	58,400	58,800	59,200	59,600	60,000	60,400
18.50 TO LESS THAN 18.75	56,900	57,300	57,700	58,100	58,500	58,900	59,300	59,700	60,100	60,500	60,900
18.75 TO LESS THAN 19.00	57,500	57,700	58,100	58,500	58,900	59,300	59,700	60,100	60,500	60,900	61,300
19.00 TO LESS THAN 19.25	57,900	58,100	58,500	58,900	59,300	59,700	60,100	60,500	60,900	61,300	61,700
19.25 AND OVER	58,300	58,500	58,900	59,300	59,700	60,100	60,500	60,900	61,300	61,700	62,100

VEHICLE WEIGHT TABLE 26 (REG)

Allowable Gross Weight On A Vehicle With Eight Or More Axles (kilograms)
Inter-Vehicle-Unit Distance, 2.7 Metres To Less Than 3.0 Metres

Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 501 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 AND INCL 10 000
LESS THAN 15.50	51,600	52,000	52,400	52,900	53,300	53,800	54,200	54,700	55,100	55,600	56,000
15.50 TO LESS THAN 15.75	52,000	52,400	52,900	53,300	53,800	54,200	54,700	55,100	55,600	56,000	56,500
15.75 TO LESS THAN 16.00	52,500	52,900	53,300	53,800	54,200	54,700	55,100	55,600	56,000	56,500	56,900
16.00 TO LESS THAN 16.25	52,900	53,400	53,800	54,200	54,700	55,100	55,600	56,000	56,500	56,900	57,400
16.25 TO LESS THAN 16.50	53,400	53,800	54,300	54,700	55,200	55,600	56,100	56,500	57,000	57,400	57,800
16.50 TO LESS THAN 16.75	53,900	54,300	54,700	55,200	55,600	56,100	56,500	57,000	57,400	57,800	58,300
16.75 TO LESS THAN 17.00	54,300	54,800	55,200	55,600	56,100	56,500	57,000	57,400	57,900	58,300	58,700
17.00 TO LESS THAN 17.25	54,800	55,200	55,700	56,100	56,500	57,000	57,400	57,900	58,300	58,700	59,200
17.25 TO LESS THAN 17.50	55,200	55,700	56,100	56,600	57,000	57,400	57,900	58,300	58,700	59,200	59,600
17.50 TO LESS THAN 17.75	55,700	56,100	56,600	57,000	57,400	57,900	58,300	58,700	59,200	59,600	60,000
17.75 TO LESS THAN 18.00	56,200	56,600	57,000	57,500	57,900	58,300	58,800	59,200	59,600	60,100	60,500
18.00 TO LESS THAN 18.25	56,600	57,100	57,500	57,900	58,400	58,800	59,200	59,600	60,100	60,500	61,000
18.25 TO LESS THAN 18.50	57,100	57,500	57,900	58,400	58,800	59,200	59,700	60,100	60,500	61,000	61,400
18.50 TO LESS THAN 18.75	57,500	58,000	58,400	58,800	59,300	59,700	60,100	60,500	61,000	61,400	61,900
18.75 TO LESS THAN 19.00	58,000	58,400	58,800	59,200	59,700	60,100	60,600	60,900	61,400	61,800	62,300
19.00 TO LESS THAN 19.25	58,400	58,800	59,200	59,600	60,100	60,500	61,000	61,300	61,800	62,200	62,700
19.25 AND OVER	58,800	59,200	59,600	60,000	60,500	60,900	61,400	61,700	62,200	62,600	63,100

VEHICLE WEIGHT TABLE 27 (REG)

Allowable Gross Weight On A Vehicle With **Eight Or More Axles** (kilograms)
Inter-Vehicle-Unit Distance, **3.0 Metres To Less Than 3.3 Metres**
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 AND INCL 10 000
LESS THAN 16.00	53,100	53,400	53,800	54,300	54,700	55,200	55,700	56,200	56,600	57,100	57,600
16.00 TO LESS THAN 16.25	53,500	53,900	54,300	54,700	55,200	55,700	56,100	56,600	57,100	57,600	58,000
16.25 TO LESS THAN 16.50	54,000	54,400	54,700	55,200	55,700	56,100	56,600	57,100	57,500	58,000	58,500
16.50 TO LESS THAN 16.75	54,400	54,800	55,200	55,700	56,100	56,600	57,100	57,500	58,000	58,500	58,900
16.75 TO LESS THAN 17.00	54,900	55,300	55,600	56,100	56,600	57,100	57,500	58,000	58,500	58,900	59,400
17.00 TO LESS THAN 17.25	55,300	55,700	56,100	56,600	57,000	57,500	58,000	58,500	58,900	59,400	59,900
17.25 TO LESS THAN 17.50	55,800	56,200	56,500	57,000	57,500	58,000	58,500	59,000	59,400	59,900	60,500
17.50 TO LESS THAN 17.75	56,300	56,600	57,000	57,500	58,000	58,500	59,000	59,500	60,000	60,500	61,000
17.75 TO LESS THAN 18.00	56,700	57,100	57,500	58,000	58,500	59,000	59,500	60,000	60,500	61,000	61,500
18.00 TO LESS THAN 18.25	57,200	57,500	57,900	58,400	58,900	59,500	60,000	60,500	61,000	61,500	62,000
18.25 TO LESS THAN 18.50	57,600	58,000	58,400	58,900	59,400	59,900	60,500	61,000	61,500	62,100	62,500
18.50 TO LESS THAN 18.75	58,100	58,400	58,800	59,300	59,900	60,400	61,000	61,500	62,100	62,600	63,000
18.75 TO LESS THAN 19.00	58,600	58,800	59,400	59,700	60,300	60,800	61,400	62,900	62,500	63,000	63,500
19.00 TO LESS THAN 19.25	59,000	59,200	59,800	60,100	60,700	61,200	61,800	62,300	62,900	63,400	63,500
19.25 AND OVER	59,400	59,600	60,200	60,500	61,100	61,600	62,200	62,700	63,300	63,500	63,500

VEHICLE WEIGHT TABLE 28 (REG)

Allowable Gross Weight On A Vehicle With Eight Or More Axles (kilograms)
Inter-Vehicle-Unit Distance, 3.3 Metres To Less Than 3.6 Metres
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	5 000 or LESS	5 001 TO LESS THAN 5 500	5 501 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500	9 500 TO AND INCL 10 000
LESS THAN 16.00	54,300	54,700	55,100	55,500	55,900	56,300	56,800	57,200	57,600	58,000	58,400
16.00 TO LESS THAN 16.25	54,700	55,200	55,600	56,000	56,400	56,800	57,200	57,700	58,100	58,500	59,000
16.25 TO LESS THAN 16.50	55,200	55,700	56,100	56,500	56,900	57,300	57,700	58,100	58,600	59,000	59,500
16.50 TO LESS THAN 16.75	55,700	56,100	56,600	57,000	57,400	57,800	58,200	58,600	59,000	59,400	59,900
16.75 TO LESS THAN 17.00	56,200	56,600	57,100	57,500	57,900	58,300	58,700	59,100	59,500	59,900	60,400
17.00 TO LESS THAN 17.25	56,600	57,100	57,600	58,000	58,400	58,800	59,200	59,600	60,000	60,400	60,900
17.25 TO LESS THAN 17.50	57,100	57,600	58,100	58,500	58,900	59,300	59,700	60,100	60,500	60,900	61,400
17.50 TO LESS THAN 17.75	57,600	58,100	58,600	59,000	59,400	59,800	60,200	60,600	61,000	61,400	61,900
17.75 TO LESS THAN 18.00	58,100	58,600	59,100	59,500	59,900	60,300	60,700	61,100	61,500	61,900	62,500
18.00 TO LESS THAN 18.25	58,600	59,100	59,600	60,000	60,400	60,800	61,200	61,600	62,100	62,500	63,000
18.25 TO LESS THAN 18.50	59,100	59,600	60,100	60,500	60,900	61,300	61,700	62,200	62,600	63,000	63,500
18.50 TO LESS THAN 18.75	59,600	60,100	60,600	61,000	61,400	61,800	62,300	62,700	63,100	63,500	63,500
18.75 TO LESS THAN 19.00	60,100	60,500	61,000	61,400	61,800	62,200	62,700	63,100	63,500	63,500	63,500
19.00 TO LESS THAN 19.25	60,600	60,900	61,400	61,800	62,200	62,600	63,100	63,500	63,500	63,500	63,500
19.25 AND OVER	61,000	61,300	61,800	62,200	62,600	63,000	63,500	63,500	63,500	63,500	63,500

VEHICLE WEIGHT TABLE 29 (REG)

Allowable Gross Weight On A Vehicle With **Eight Or More Axles** (kilograms)
Inter-Vehicle-Unit Distance, **3.6 Metres Or More**
Front Axle Weight, (kilograms)

BASE LENGTH, (METRES)	Front Axle Weight, (kilograms)									
	5 000 or LESS	5 001 TO LESS THAN 5 500	5 500 TO LESS THAN 6 000	6 000 TO LESS THAN 6 500	6 500 TO LESS THAN 7 000	7 000 TO LESS THAN 7 500	7 500 TO LESS THAN 8 000	8 000 TO LESS THAN 8 500	8 500 TO LESS THAN 9 000	9 000 TO LESS THAN 9 500
LESS THAN 16.00	54,800	55,200	55,600	56,000	56,400	56,800	57,300	57,700	58,100	58,500
16.00 TO LESS THAN 16.25	55,200	55,700	56,100	56,500	56,900	57,300	57,700	58,200	58,600	59,000
16.25 TO LESS THAN 16.50	55,700	56,200	56,600	57,000	57,400	57,800	58,200	58,600	59,100	59,500
16.50 TO LESS THAN 16.75	56,200	56,600	57,100	57,500	57,900	58,300	58,700	59,100	59,500	59,900
16.75 TO LESS THAN 17.00	56,700	57,100	57,600	58,000	58,400	58,800	59,200	59,600	60,000	60,400
17.00 TO LESS THAN 17.25	57,100	57,600	58,100	58,500	58,900	59,300	59,700	60,100	60,500	60,900
17.25 TO LESS THAN 17.50	57,600	58,100	58,600	59,000	59,400	59,800	60,200	60,600	61,000	61,400
17.50 TO LESS THAN 17.75	58,100	58,600	59,100	59,500	59,900	60,300	60,700	61,100	61,500	61,900
17.75 TO LESS THAN 18.00	58,600	59,100	59,600	60,000	60,400	60,800	61,200	61,600	62,000	62,400
18.00 TO LESS THAN 18.25	59,100	59,600	60,100	60,500	60,900	61,300	61,700	62,100	62,600	63,000
18.25 TO LESS THAN 18.50	59,600	60,100	60,600	61,000	61,400	61,800	62,200	62,700	63,100	63,500
18.50 TO LESS THAN 18.75	60,100	60,600	61,100	61,500	61,900	62,300	62,700	63,200	63,500	63,500
18.75 TO LESS THAN 19.00	60,600	61,000	61,500	61,900	62,300	62,700	63,100	63,500	63,500	63,500
19.00 TO LESS THAN 19.25	61,100	61,400	61,900	62,300	62,700	63,100	63,500	63,500	63,500	63,500
19.25 AND OVER	61,500	61,800	62,300	62,700	63,100	63,500	63,500	63,500	63,500	63,500

AUTHORITY AND PENALTIES

Sections 124, 125 and 126, Highway Traffic Act

124. (1) Where a police officer or officer appointed for carrying out the provisions of this Act has reasonable and probable grounds to believe that the gross vehicle weight of a vehicle or combination of vehicles is in excess of the limits permitted under this Act or the regulations or a permit issued for the vehicle or combination of vehicles, he or she may weigh the same, by means of either portable or stationary scales, and may require that the vehicle or combination of vehicles be driven to the nearest weigh scales.

(2) Subsection (1) does not apply where the driver of a commercial motor vehicle produces an inventory showing the true gross vehicle weight of the vehicle or combination of vehicles.

(3) Where a police officer or officer appointed for carrying out the provisions of this Act has reasonable and probable grounds to question the validity of any documents produced in accordance with subsection (2), or to believe the axle unit weight or axle group weight of a vehicle or combination of vehicles is in excess of the limits permitted under this Act or the regulations or a permit issued for the vehicle or combination of vehicles, he or she may weigh the same by means of either portable or stationary scales, and may require that the vehicle or combination of vehicles be driven to the nearest weigh scales.

(4) To determine whether the gross vehicle weight, axle unit weight or axle group weight of any vehicle or combination of vehicles is in excess of the limits permitted under this Act or the regulations or the permit issued for

the vehicle or combination of vehicles, the police officer or officer appointed for carrying out the provisions of this Act may conduct the examination that is necessary to ascertain the distance between the axles of the vehicles or combination of vehicles.

(5) Where it is found that the gross vehicle weight, axle unit weight or axle group weight of any vehicle or combination of vehicles is in excess of the limits permitted under this Act or the regulations, or the permit issued for the vehicle or combination of vehicles, the police officer or officer appointed for carrying out the provisions of this Act may require the driver to redistribute or remove so much of the load as is necessary to ensure compliance with this Act, the regulations and the permit.

(6) Every driver who, when required under subsection (1) or (3) to proceed to a weigh scale, refuses or fails to do so is guilty of offence and on conviction is liable to a fine of not less than \$200 and not more than \$1,000 and to the suspension of his or her driver's licence for a period of not more than thirty days.

(7) Every driver who,

- (a) when required under subsection (5) to redistribute or remove part of a load refuses or fails to do so or to make arrangements to do so; or
- (b) obstructs any weighing, measuring or examination authorized by this section,

is guilty of an offence and on conviction is liable to a fine of not less than \$100 and not more than \$200.

125. Penalty

Every person who contravenes subsection 115(1) sections 116, 117 and 118, subsection 119 (4), section 120 or subsection 122 (1), (2) or (3) or a regulation made under subsection 123 (1) or a by-law made under subsection 123(2) is guilty of an offence and on conviction is liable to a fine of,

- (a) \$2 per 100 kilograms, or part thereof, for any weight in excess of that permitted under this Act or the regulations, where the overweight is less than 5,000 kilograms, but in no case shall the fine be less than \$50;
- (b) \$4 per 100 kilograms, or part thereof, for any weight in excess of that permitted under this Act or the regulations, where the overweight is 5,000 kilograms or more but is less than 7,500 kilograms;
- (c) \$6 per 100 kilograms, or part thereof, for any weight in excess of that permitted under this Act or the regulations, where the overweight is 7,500 kilograms or more but is less than 10,000 kilograms;
- (d) \$8 per 100 kilograms, or part thereof, for any weight in excess of that permitted under the Act or in the regulations, where the overweight is 10,000 kilograms or more but is less than 15,000 kilograms; and
- (e) \$10 per 100 kilograms, or part thereof, for any weight in excess of that permitted under this Act or the regulations, where the overweight is 15,000 kilograms or more.

126. Overloading by consignor

Every consignor of goods, or the consignor's agent or employee, who causes a vehicle or combination of vehicles not owned by the consignor to be loaded so that when operated on a highway,

- (a) the weight on any millimetre in the width of the tire exceeds a limit set out in subsection 115(1) or in the regulations;
- (b) the axle unit weight on an axle unit exceeds a limit set out in section 116 or 119 or in the regulations;
- (c) an axle group weight exceeds a limit set out in section 117 or 119 or in the regulations;
- (d) the gross vehicle weight exceeds a limit set out in section 118 or 119 or in the regulations; or
- (e) the gross vehicles weight exceeds the gross vehicle weight specified in a permit referred to in section 121

is guilty of an offence and on conviction is liable to a fine as if the consignor had been convicted under section 125. (Bill 179).

VICTIM FINE SURCHARGE RATES

This surcharge is applied to all provincial offences except parking and is added to the set fine amount.

For Set Fines of	Add Surcharge
0 - \$ 50	\$ 5.00
\$ 51 - \$ 75	\$ 10.00
\$ 76 - \$ 100	\$ 15.00
\$ 101 - \$ 150	\$ 20.00
\$ 151 - \$ 200	\$ 30.00
\$ 201 - \$ 250	\$ 40.00
\$ 251 - \$ 300	\$ 50.00
\$ 301 - \$ 350	\$ 60.00
\$ 351 - \$ 400	\$ 70.00
\$ 401 - \$ 450	\$ 80.00
\$ 451 - \$ 500	\$ 90.00
\$ 501 - \$ 1000	\$ 100.00
\$ 1000 +	20% of actual fine imposed

PART TWO

VEHICLE & LOAD DIMENSIONS

ONTARIO HIGHWAY TRAFFIC ACT

PART VII

LOAD AND DIMENSIONS

108. In this Part,

“box length”, in a combination of vehicles having more than one trailer, means the external measurement from the front of the foremost trailer to the rear of the rearmost trailer, including load, but excluding any portion of auxiliary equipment or machinery that extends beyond the front of the foremost trailer and that is not designed or used for the transportation of goods.

“over-dimensional farm vehicle” means a farm tractor, self-propelled implement of husbandry, implement of husbandry, or any combination of them, having a weight, width, length or height in excess of the limits provided in this Part or Part VIII;

“semi-trailer” means a trailer designed so that its forward part rests on or is carried by another vehicle or trailer converter dolly to which it is coupled by means of a fifth wheel assembly.

109. (1) Subject to section 110, no vehicle including load or contents shall have a greater width than 2.6 metres while on a highway except,

- (a) traction engines, which may have a total width not exceeding 2.8 metres; or

- (b) road service vehicles as defined in Part X and this includes the vehicles while they are travelling to and from a maintenance site or repair centre.

(2) Subject to section 110, no load on a vehicle shall have a greater width than 2.6 metres while on a highway except,

- (a) loads of raw forest products which shall not exceed a total width of 2.7 metres at point of origin and which shall not exceed a total width of 2.8 metres at any time during transit; or
- (b) loads of loose fodder.

(3) Where a commercial motor vehicle is equipped with one or more rear vision mirrors that extend in whole or in part beyond either side of the vehicle, or one or more lamps, required by this Act, that extend in the whole or in part beyond either side of the vehicle, the amount of the extension shall not be included in determining the maximum width of the vehicle under subsection (1).

(4) Where a bus is equipped with rear vision mirrors, side marker lamps, side marker reflectors, side mounted turn indicators or rubber fenders around the outer edges of its wheel housings, any of which extend in whole or in part beyond either side of the vehicle, the amount of the extension shall not be included in determining the maximum width of the vehicle under subsection (1).

(5) Where a commercial motor vehicle or trailer is equipped with a load covering mechanism, extensions in the width of the vehicle caused by the mechanism shall

not be included in determining the width of the vehicle under subsection (1) where the mechanism does not extend the width of the vehicle on either side by more than 102 millimetres.

(6) Subject to section 110, no vehicle, other than a fire apparatus, a semi-trailer or a bus, including load, shall exceed the length of 12.5 metres while on a highway.

(7) No combination of vehicles, including load, coupled together shall exceed the total length of twenty-three metres while on a highway.

(7.1) Despite subsection (7), a combination of vehicles whose configuration, weight and dimensions are as prescribed by **regulation** may have a total length while on a highway, including load, that does not exceed 25 metres.

SPECIFIED REGULATION IS ON PAGE 11

(8) No combination of vehicles composed of more than one trailer shall have a box length in excess of 18.5 metres while on a highway.

(8.1) Despite subsection (8), a combination of vehicles whose configuration, weight and dimensions are as prescribed by regulation may have a box length that does not exceed 20 metres while on a highway.

(8.2) Despite subsection (8), a combination of vehicles, such that the distance from the back of the driver's compartment to the back of the combination of vehicles exceeds 19 metres, may be operated on a highway if the distance from the centre of the kingpin of the foremost trailer to the rearmost part of the combination of vehicles does not exceed 16.75 metres.

(8.3) For the purposes of subsection (8.2), a sleeping compartment shall be considered part of the driver's compartment.

(9) Subsections (8.2) and (8.3) do not apply after December 31, 1998.

(10) Subject to section 110, no semi-trailer shall have a length with an external measurement, excluding any portion of auxiliary equipment or machinery that extends beyond the front or rear of the semi-trailer and that is not designed or used for the transportation of goods, that exceed 14.65 metres while on a highway.

(10.1) Subsection (10) does not apply to a semi-trailer designed to carry vehicles.

(10.2) Despite subsection (10), a semi-trailer used in a combination of vehicles whose configuration, weight and dimensions are as prescribed by regulation may have a length with an external measurement, excluding any portion of auxiliary equipment or machinery that extends beyond the front of the semi-trailer and that is not designed or used for the transportation of goods, that does not exceed 16.2 metres while on a highway.

(11) No bus, other than an articulated bus, shall exceed the length of 12.5 metres while on a highway, but an increase in the length of a bus caused by the addition of a liquid filled or other energy-absorbing bumper shall not be included in determining the length of the bus.

(11.1) Despite subsection (11), a bus that meets the requirements prescribed by regulation may exceed the length of 12.5 metres.

(12) The council of a city may by by-law prohibit the operation of a combination of vehicles having a total length, including load, in excess of 15.25 metres while on a highway or a portion thereof under its jurisdiction designated in the by-law.

(13) Where a vehicle is equipped with one or more mirrors that extend in whole or in part beyond the front of the vehicle, the amount of the extension shall not be included in determining the length of the vehicle under subsection (6), (11) or (12).

(14) Subject to section 110, no vehicle including load shall have a greater height than 4.15 metres while on a highway.

(15) Every person who contravenes this section is guilty of an offence and on conviction is liable to fine of not less than \$200 and not more than \$1,000 and, in addition, the permit issued for the vehicle under section 7 may be suspended for not more than six months.

(16) The Lieutenant Governor in Council may make regulations (Reg. 32/94) for the purposes of subsection (7.1), (8.1) and (10.2),

- (a) prescribing configurations of vehicles and combinations of vehicles;
- (b) setting limits on dimensions of vehicles and combinations of vehicles, except those dimensions already set out in this Act;
- (c) prescribing requirements for components and equipment for vehicles and combinations of vehicles.

(17) The Lieutenant Governor in Council may make regulations prescribing requirement for the purpose of subsection (11.1), including prescribed maximum length bus type and use, load distribution, configurations and requirements for components, equipment and safety features.

110. (1) The municipal corporation or other authority having jurisdiction over the highway may, upon application in writing, grant a permit for the moving of heavy vehicles, loads, objects or structures in excess of the dimensional limits set out in section 109 or the weight limits set out in Part VIII.

(2) The permit referred to in subsection (1) may be general, or may limit the time and the particular highway that may be used, and may contain conditions relating to the protection of persons and property from injury or damage and the municipal corporation or other authority may require a bond or other security sufficient to cover the cost of repairing any possible damage to the highway.

(3) The council of any municipality may by by-law provide that a permit referred to in subsection (1) may be issued by an officer of the corporation named therein.

(4) In the case of a vehicle for which a permit is required under this section in order to pass over a highway or highways under the jurisdiction of two or more municipalities or other authorities, the permit so to do may be issued by the Ministry, which permit is instead of the several permits to be otherwise obtained from the municipal corporations or other authorities, and the permit may limit the time and the particular highway or highways that may be used, and may contain any special con-

ditions or provisions that may be considered necessary to protect the highways from damage, and the Ministry may require a bond or other security sufficient to cover the cost of repairing possible damage to the highway.

(5) The owner, operator or mover of a heavy vehicle, load, object or structure in respect of which a permit is granted under this section is nevertheless responsible for all damages that may be caused to the highway by reason of the driving, operating or moving of any such heavy vehicle, load, object or structure.

(6) It is a condition of every permit issued under this section that the original of the permit be carried in the vehicle for which the permit was issued and be produced when demanded by a police officer or an officer appointed for carrying out the provisions of this Act.

(7) Every person who operates or permits the operation of a vehicle or combination of vehicles contrary to any of the conditions of the permit is guilty of an offence and on conviction is liable to a fine of not less than \$100 and not more than \$500 and, in addition, if the condition contravened is in respect of any weight allowed under the permit, a fine shall be imposed as if the person had not been issued a permit under this section and had been convicted of an offence under section 116, 117 or 118 in respect of any gross vehicle weight, axle unit weight or axle group weight in excess of the maximum allowable weights permitted under this Act or the regulations.

111. (1) Every vehicle carrying a load which overhangs the rear of the vehicle to the extent of 1.5 metres or more while on a highway shall display upon the overhanging load at the extreme rear end thereof at any time from one-half hour before sunset to one-half hour after sunrise, or

at any other time when there is insufficient light or unfavourable atmospheric conditions, a red light, and at all other times a red flag or a red marker sufficient to indicate the projection of the load.

111. (2) No person shall operate or permit to be operated upon a highway any motor vehicle or trailer unless the load that the vehicle or trailer is carrying is firmly bound, sufficiently covered, or otherwise secured or loaded, so that no portion of the load may become dislodged or fall from the motor vehicle or trailer.

(3) The Lieutenant Governor in Council may make regulations, Reg. 577 - covering of loads and 614 security of loads).

- (a) prescribing the manner of loading, and of covering and securing loads on vehicles or classes of vehicles operated on highways or classes of highways;
- (b) designating the vehicles or classes of vehicles and the highways or classes of highways to which any loading, covering or securing provisions are to apply; and
- (c) prescribing classes of vehicles, highways and loads for the purposes of clauses (a) and (b).

(4) Every person who contravenes this section or a regulation made under subsection (3) is guilty of an offence and on conviction is liable to a fine of not less than \$100 and not more than \$200 and, in addition, his or her driver's licence issued under section 32 and the person's permit issued under section 7 may be suspended for a period of not more than sixty days.

112. (1) The Lieutenant Governor in Council may make regulations,

- (a) classifying and defining explosives and dangerous materials;
- (b) regulating or prohibiting the transportation of explosives and dangerous materials or any class thereof by a vehicle on a highway;
- (c) regulating the preparation and packaging of explosives and dangerous materials or any class thereof to be transported by a vehicle on a highway; and
- (d) requiring the labelling of packages and containers of explosives and dangerous materials of any class thereof and prescribing the labels to be attached to such packages and containers.

(No regulations made, see Dangerous Goods Transportation Act).

(2) Any regulation made under subsection (1) may adopt by reference, in whole or in part, with the changes that the Lieutenant Governor in Council considers necessary, any code or standard, or any regulation made by the Government of Canada, and may require compliance with any code, standard or regulation that is so adopted.

(3) Every person who contravenes a regulation made under this section is guilty of an offence and on conviction is liable to a fine of not less than \$100 and not more than \$500 or to imprisonment for a term of not more than three months, or to both.

113. (1) This Part, other than regulations made under this section, does not apply to over-dimensional farm vehicles.

(2) The Lieutenant Governor in Council may make regulations, (Reg. 603).

- (a) regulating or prohibiting the movement of over-dimensional farm vehicles or classes thereof on a highway or on classes of highways;
- (b) requiring that escort vehicles or classes of escort vehicles accompany over-dimensional farm vehicles or classes thereof on a highway or classes of highways;
- (c) prescribing the types, specifications and locations of markings, signs and lights that shall be carried by over-dimensional farm vehicles and escort vehicles or classes of either or both of them on a highway or classes of highways;
- (d) prescribing conditions for the movement of over-dimensional farm vehicles on a highway or classes of highways relating to the protection of persons and property from injury or damage.

REGULATION 32/94
VEHICLE CONFIGURATIONS

ONTARIO REGULATION 32/94

VEHICLE CONFIGURATIONS

1. In this Regulation,

“axle spread” means the longitudinal distance between the centres of the foremost and rearmost axles of an axle unit;

“effective overhang” means the longitudinal distance from the turn centre of the trailer to its rearmost point, including any load;

“fifth wheel assembly” means a plate-type coupling device comprised of a kingpin, locking jaws and plates whose lower half is mounted on the rear portion of a vehicle frame or the frame of a trailer converter dolly and whose upper half is fastened to the underside of the forward portion of a semi-trailer for the purpose of supporting and towing the semi-trailer;

“full trailer” means a trailer designed so that its own weight and any load are carried on its own axles and includes a combination consisting of a semi-trailer and a trailer converter dolly;

“inter-axle spacing” means the longitudinal distance separating two consecutive axle units within a vehicle or combination of vehicles, measured from the centre of the rearmost axle of the foremost axle unit to the centre of the foremost axle of the other axle unit;

“liftable axle” means an assembly of two or more wheels whose centres are in one transverse vertical plane that is equipped with a device for altering (other than by longitudinal movement of the assembly only) the weight transmitted to the highway surface and that may be able to lift its tires from contact with that surface;

“self-steering axle” means an assembly of two or more wheels whose centres are in one transverse vertical plane and whose wheels can articulate in response to forces generated between the tires and the road or through mechanisms and linkages that operate independently of the driver;

“swing radius” means the greatest horizontal distance from the vertical axis through the centre of the kingpin to any point on the semi-trailer ahead of the kingpin, including load and any extension to the length caused by auxiliary equipment or machinery;

“tandem axle” means a “dual axle” as defined in Part VIII that does not include a liftable axle or a self-steering axle and that has the same number of tires on each wheel;

“track width” means the width of an axle across the outside faces of the tires measured at any point above the lowest point of the rim;

“tridem axle” means a “triple axle” as defined in Part VIII that does not include a liftable axle or a self-steering axle and that has the same number of tires on each wheel;

“turn centre” means the geometric centre of the axle unit on a semi-trailer or of the rear axle unit on a tractor or a full trailer;

“wheelbase” means the longitudinal distance,

- (a) from the centre of the kingpin to the turn centre in the case of a semi-trailer;
- (b) from the centre of the front axle to the turn centre in the case of a tractor;
- (c) from the centre of articulation of the turnable to the turn centre in the case of a full trailer.

2. Rearmost trailer in a combination of vehicles

The rearmost trailer in a combination of vehicles described in this regulation shall be equipped with a rear impact guard if the trailer is built after July 14, 1993 and,


- (a) it has an axle unit that can slide or is fixed so that the rear of the rearmost tire is more than 0.3 metres in front of the rear of the trailer; and
- (b) its rear structure is more than 0.56 metres above the ground when the trailer is unladen on a level surface.

3. Rear Impact Guard on a trailer

A rear impact guard on a trailer, as shown in Figure 1, shall meet the standards for such a guard under the Motor Vehicle Safety Act (Canada) or the standards under the United States Federal Motor Vehicle Safety Standards but, in the absence of such standards, it shall consist of a single horizontal beam that is rigidly attached to the trailer and that,

- (a) extends within 0.1 metres of each side of the trailer;
- (b) is not more than 0.3 metres in front of the rear of the trailer and as close to its rear as practicable; and
- (c) is not more than 0.56 metres above the ground when the trailer is unladen on a level surface.



Figure 1 - Rear Impact Guard Requirements



4. **Conspicuity markings**

Conspicuity markings, as shown in Figure 2, shall be in accordance with United States Federal Motor Vehicle Safety Standard 108 S5.7 that became effective on December 1, 1993 or with a corresponding standard, if any under the Motor Vehicle Safety Act (Canada).

Figure 2 - Conspicuity Markings



- Alternating red and white reflective tape 5 cm wide along the sides and rear of the trailer
- As close to 1.2 m above the road as possible
- Must cover at least half the trailer length
- No more than two thirds in one colour
- Pattern need not be as illustrated provided it meets the above requirements
- Alternating red and white reflective tape along the rear impact guard or bumper
- White chevron 30 cm long in upper corners of rear


5. **Wheels**

All wheels on all vehicles and trailer converter dollies described in this regulation and manufactured after October 19, 1994 shall be fitted with a system of automatic brake adjustment and brake adjustment indicators in accordance with United States Federal Motor Vehicle Safety Standard 121 S5.18 or S5.2.2 or with a corresponding standard, if any, under the Motor Vehicle Safety Act (Canada).

6. Tractor-Semi-trailer

A combination of vehicles composed of a tractor and a semi-trailer, as shown in Figure 3, may be operated on a highway if the requirements of section 7, 8, and 9 are met.

Figure 3 - Tractor-Semi-trailer



7.(1) Tractor

The tractor shall have as its front axle one axle equipped with single tires and as its drive axle one axle or a tandem axle that has an axle spread of 1.2 to 1.85 metres.

7.(2)

The tractor's inter-axle spacing from its front axle shall not be less than 3 metres and its wheelbase shall not be greater than 6.2 metres.

7.(3)

The tractor shall not be equipped with a liftable axle or a self-steering axle, whether raised, lowered or rendered inoperative.

8.(1) **Semi-trailer**

The semi-trailer shall have one axle, a tandem axle that has an axle spread of 1.2 to 1.85 metres or a tridem axle that has an axle spread of 2.4 to 3.7 metres and, if the semi-trailer's width exceeds 2.5 metres, all of its axles shall have a track width of at least 2.5 metres.

8.(2)

The swing radius of the semi-trailer shall not be greater than 2 metres, its wheelbase not greater than 12.5 metres and its effective overhang, including load, not greater than 35 per cent of its wheelbase.

8.(3)

The semi-trailer shall not be equipped with a lift-able axle or a self-steering axle, whether raised, lowered or rendered inoperative.

8.(4)

A semi-trailer built after July 14, 1993 shall have the conspicuity markings indicated in section 4.

9. **Combination of vehicles**

The combination of vehicles, including load, shall not exceed 23 metres in length and the weight on any tire in the combination shall not exceed 3,000 kilograms.

10.(1) **A-train double**


An A-train double, as shown in Figure 4, shall be composed of a tractor, a semi-trailer and,

- (a) a trailer converter dolly that is towed from a single hitch on the centre line of the semi-trailer and another semi-trailer; or
- (b) a full trailer attached to the semi-trailer as if a trailer converter dolly were used and towed from a single hitch on the centre line of the semi-trailer.

10.(2)

An A-train double may be operated on a highway if the requirements of sections 11 to 14 are met.

Figure 4 - A-Train Double



Note: (1) Inter-axle spacings

Single to single	minimum 3.0 m
Single to tandem	minimum 3.0 m
Tandem to tandem	minimum 5.0 m

(2) Tandem axle spread from 1.2 to 1.85 m

(3) Second trailer weight not greater than 16 000 kg, or the weight of the lead trailer, whichever is least

11. Tractor of an A-train

The tractor of an A-train double shall meet the requirements set out in section 7.

12.(1) Foremost semi-trailer

The foremost semi-trailer shall have one axle or a tandem axle that has an axle spread of 1.2 to 1.85 metres and, if the semi-trailer's width exceeds 2.5 metres, all of its axles shall have track width of at least 2.5 metres.

12.(2)

The inter-axle spacing from the tractor drive axle unit shall be at least,

- (a) 3 metres, if one of the axle units has only one axle;
- (b) 5 metres, if both axle units are tandem axles.

12.(3)

The swing radius of the foremost semi-trailer shall not be greater than 2 metres, its wheelbase not less than 6.5 metres and its hitch offset not greater than 1.8 metres.

12.(4)

The foremost semi-trailer shall not be equipped with a liftable axle or a self-steering axle, whether raised, lowered or rendered inoperative.

12. (5)

In this section, “hitch offset” means the longitudinal distance from the turn centre of the foremost semi-trailer to the articulation point of the hitch used to tow the rearmost trailer.

13.(1) Rearmost trailer

The rearmost trailer shall have one axle at the front and one axle or a tandem axle that has an axle spread of 1.2 to 1.85 metres at the rear and, if the trailer's width exceeds 2.5 metres, all of its axles shall have a track width of at least 2.5 metres.

13.(2)

The wheelbase of the rearmost trailer shall not be less than 6.5 metres and the inter-axle spacing from its foremost axle unit shall not be less than 3 metres.

13.(3)

The rearmost trailer shall not be equipped with a liftable axle or a self-steering axle, whether raised, lowered or rendered inoperative.

13.(4)

The gross vehicle weight of the rearmost trailer shall not exceed that of the foremost semi-trailer or 16,000 kilograms, whichever is less.

14.(1) A-train double

The box length of an A- train double shall not exceed 18.5 metres and the weight on any of its tires shall not exceed 3,000 kilograms.

14.(2)

A trailer built after July 14, 1993 that forms part of an A-train double shall have the conspicuity markings indicated in section 4.

14.(3)

The gross vehicle weight of an A-train double shall be calculated as set out in the Act, except that, for the purposes of that calculation, the front axle load is the lesser of the actual front axle load and 5499 kilograms and the gross vehicle weight shall not exceed,

- (a) 39,700 kilograms, if there are five axles;
- (b) 47,600 kilograms, if there are six axles;
- (c) 53,500 kilograms, if there are seven or eight axles.


15.(1) B-train double

A B-train double, as shown in Figure 5, shall be composed of a tractor and two semi-trailers, the rearmost of which is attached by a fifth wheel assembly whose lower half is mounted on the rear of the foremost semi-trailer.

15.(2)

A B-train double may be operated on a highway if the requirements of sections 16 to 19 are met.

Figure 5 - B-Train Double



Note: (1) Inter-axle spacings

- | | |
|-----------------------------------|--------------------------------|
| Single to single | minimum 3.0 m |
| Single to tandem | minimum 3.0 m |
| Single to tridem | minimum 3.0 m |
| Tandem to tandem | minimum 5.0 m |
| Tandem to tridem | minimum 5.5 m |
| (2) Tandem axle spread | from 1.2 to 1.85 m |
| Tridem axle spread | from 2.4 to 3.1 m |
| (3) Sum of semitrailer wheelbases | limited to a maximum of 17.0 m |

16. **Tractor**

The tractor shall meet the requirements set out in section 7.

17.(1) **Foremost semi-trailer**

The foremost semi-trailer shall have a tandem axle that has an axle spread of 1.2 to 1.85 metres or a tridem axle that has an axle spread of 2.4 to 3.1 metres and all of its axles shall have a track width of at least 2.5 metres.

17.(2)

The swing radius of the foremost semi-trailer shall not be greater than 2 metres and its wheelbase not less than 6.5 metres.

17.(3)

The inter-axle spacing from the tractor drive axle unit shall be at least,

- (a) three metres, if one of the axle units has only one axle;
- (b) five metres, if both axle units are tandem axles;
- (c) 5.5 metres, if the axle units are a tandem axle and a tridem axle.

17.(4)

The foremost semi-trailer shall not be equipped with a liftable axle or a self-steering axle, whether raised, lowered or rendered inoperative.

18.(1) **Rearmost semi-trailer**

The rearmost semi-trailer shall have one axle or a tandem axle that has an axle spread of 1.2 to 1.85 metres and all of its axles shall have a track width of at least 2.5 metres.

18.(2)

The rearmost semi-trailer shall have a wheelbase that is not less than 6.25 metres.

18.(3)

The inter-axle spacing from the foremost semi-trailer axle unit shall be at least,

- (a) three metres, if one of the axle units has only one axle;
- (b) five metres, if both axle units are tandem axles;
- (c) 5.5 metres, if the axle units are a tandem axle and a tridem axle.

18.(4)

The rearmost semi-trailer shall not be equipped with a liftable axle or a self-steering axle, whether raised, lowered or rendered inoperative.

19.(1) **B-train double**

The box length of a B-train double shall not exceed 20 metres and the weight on any of its tires shall not exceed 3,00 kilograms.

19.(2)

The sum of the wheelbases of a B-train double's semi-trailers shall not exceed seventeen metres.

19.(3)

Any trailer built after July 14, 1993 that forms part of a B-train double shall have the conspicuity markings indicated in section 4.

19.(4)

The gross vehicle weight of a B-train double shall be calculated as set out in the Act, except that, for the purposes of that calculation, Table A shall be used instead of Table 27 of Regulation 597 of the Revised Regulations of Ontario, 1990 if there are seven axles and Table B shall be used instead of Table 34 of that Regulation if there are eight axles.

Table A

**Allowable Gross Weight
on a B- train with 7 Axles**

Base Length (metres)	Front Axle Weight (kilograms)	
	5 000 or less	5 001 to and including 6 000
Less than 17.00	55 900	56 500
17.00 to less than 17.25	56 300	56 600
17.25 to less than 17.50	56 700	57 000
17.50 to less than 17.75	57 100	57 400
17.75 to less than 18.00	57 500	57 800
18.00 to less than 18.25	57 900	58 200
18.25 to less than 18.50	58 400	58 600
18.50 to less than 18.75	58 800	59 000
18.75 to less than 19.00	59 300	59 500
19.00 to less than 19.25	59 700	59 900
19.25 and over	60 100	60 300

Table B

**Allowable Gross Weight
on a B-train with 8 Axles**

Base Length (metres)	Front Axle Weight (kilograms)	
	5 000 or less	5 001 to and including 6 000
Less than 19.00	60 600	61 000
19.00 to less than 19.25	61 100	61 400
19.25 to less than 19.40	61 500	61 800
19.40 to less than 19.75	61 700	62 500
19.75 to less than 20.00	62 100	62 900
20.00 to less than 20.25	62 300	63 100
20.25 to less than 20.50	62 600	63 300
20.50 to less than 20.75	62 900	63 500
20.75 to less than 21.00	63 100	63 500
21.00 to less than 21.25	63 300	63 500
21.25 and over	63 500	63 500


20.(1) C-train double

A C-train double, as shown in Figure 6, shall be composed of a tractor and two semi-trailers the second of which is attached to the first by a trailer converter dolly with a frame rigid in the horizontal plane that is towed from two hitches located in a horizontal transverse line on the foremost semi-trailer that preclude any rotation in the horizontal plane about the hitch points.

20.(2)

A C-train double may be operated on a highway if the requirements of sections 21 to 25 are met.

Figure 6 - C-Train Double



Note: (1) Inter-axle spacings

Single to single	minimum 3.0 m
Single to tandem	minimum 3.0 m
Tandem to tandem	minimum 5.0 m

(2) Tandem axle spread from 1.2 to 1.85 m

(3) Second trailer weight not greater than 21 000 kg, or the weight of the lead trailer, whichever is least

(4) Combined weight on the dolly axle and a tandem axle on the lead trailer not greater than 23 000 kg

21.

The tractor of a C-train double shall meet the requirements set out in section 7.

22.

The foremost semi-trailer shall meet the requirements set out in subsections 12(1), (2), (3) and (4) and, in addition, it shall have a hitch that meets the requirements of section 904 of the Motor Vehicle Safety Act (Canada).

23.(1) Trailer converter dolly

The trailer converter dolly referred to in subsection 20(1) shall be equipped with a drawbar that does not exceed 2 metres in length and the trailer converter dolly shall meet the requirements of section 903 of the Motor Vehicle Safety Act (Canada).

23.(2)

The track width of the trailer converter dolly shall be at least 2.5 metres if the width of the rearmost semi-trailer exceeds 2.5 metres.

23.(3)

In this section, “drawbar” means a towing structure that is connected to the chassis frame of the trailer converter dolly that includes an eye or equivalent device for coupling to a trailer hitch.

24.(1) Rearmost semi-trailer

The rearmost semi-trailer shall have one axle or a tandem axle that has an axle spread of 1.2 to 1.85 metres and, if the width of the semi-trailer exceeds 2.5 metres, all of its axles shall have a track width of at least 2.5 metres.

24.(2)

The rearmost semi-trailer shall have a wheelbase of at least 6.5 metres.

24.(3)

The gross vehicle weight of the rearmost semi-trailer shall not exceed that of the foremost semi-trailer or 21,000 kilograms, whichever is less.

24.(4)

The rearmost semi-trailer shall not be equipped with a liftable axle or a self-steering axle, whether raised, lowered or rendered inoperative.

25.(1) C-train double

The box length of a C-train double shall not exceed 20 metres.

25.(2)

The weight on any tire of a C-train double shall not exceed 3,000 kilograms and the combined weight on a tandem axle on the foremost semi-trailer and on the trailer converter dolly axle shall not exceed 23,000 kilograms.

25.(3)

Any semi-trailer built after July 14, 1993 that forms part of a C-train double shall have the conspicuity markings indicated in section 4.

25.(4)

The gross vehicle weight of a C-train double shall be calculated as set out in the Act, except that, for

the purposes of that calculation, the front axle load is the lesser of the actual front axle load and 5,499 kilograms and the gross vehicle weight shall not exceed,

- (a) 41,900 kilograms, if there are five axles;
- (b) 49,800 kilograms, if there are six axles;
- (c) 54,600 kilograms, if there are seven axles;
- (d) 58,500 kilograms, if there are eight axles.

Buses

26.(1) Buses

A bus, as shown in Figure 7, commonly known as an inter-city motor coach, may be operated on a highway if it meets the requirements of this section.

26.(2)

The bus shall be equipped with motive power mounted to the rear of the front axle, air-ride or torsion-bar suspension, reclining seats and a baggage area that is separated from the passenger cabin.

26.(3)

The total length of the bus, including bumpers, shall not exceed 14 metres.

26.(4)

The bus shall have three axles and any tandem axle or two axle group shall have an axle spread of 1.2 to 1.85 metres.


26. (5)

The longitudinal distance between the geometric centre of a dual axle or a two axle group and the rear of the bus, including bumpers, shall not exceed 4 metres.

26. (6)


Any two axle group shall distribute the load it carries between the axles in a ratio corresponding to the number of tires on each axle.

Figure 7 - Intercity Motor Coach



NOTES

Road Safety



 Ontario

